


DETAIL OF SPLICE JOINT




DETAIL OF STANDARD WASHER


- 1/16 " x 1" ELLIPTICAL, SLOTTED HOLE

NOTES:

ALL HARDWARE IS TO BE GALVANIZED IN ACCORDANCE WITH THE SPECIFICATIONS.

THE GUARDRAIL AND MEDIAN BARRIER COMPONENTS DEPICTED IN ARTBA TECHNICAL BULLETIN NUMBER 268B MAY BE SUBSTITUTED IF INTERCHANGEABLE WITH THE STANDARDS FOR GUARDRAIL (GR) OR MEDIAN BARRIER (MB) AND APPROVED BY THE ENGINEER.





L= 1/4" FOR SPLICE BOLT-FULL LENGTH THREADS

L= 2" FOR SPLICE BOLT-FULL LENGTH THREADS ON NESTED W BEAMS.

L= 10" FOR STEEL POST BOLT-11/2" MIN. THREADS

L= 18" FOR WOOD AND CONCRETE POST BOLT-21/2" MIN. THREADS

L= 26" FOR MB WOOD OR CONCRETE POST-2" MIN. THREADS

DETAIL OF BUTTON HEAD BOLT AND RECESS NUT (GUARDRAIL BOLT)

	SPECIFICATION REFERENCE	STANDARD GUARDRAIL HARDWARE	ROAD AND BRIDGE STANDARDS	
	221	317114071110 3371110117112 1171110 1471112	REVISION DATE	SHEET 1 OF 3
	505	VIRGINIA DEPARTMENT OF TRANSPORTATION	01/14	501.01