FUNCTIONAL CLASSIFICATION OF ROADS SYSTEM UNDER WHICH PIPE IS TO BE INSTALLED							
RURAL PRINCIPAL AR		LOWER FUNCTIONAL CLASS - LFC RURAL LOCAL ROADS, URBAN LOCAL STREETS, SUBDIVISION STREETS WITH AN ADT LESS THAN OR EQUAL TO 4000		ENTRANCE PIPE			
ALLOWABLE PIPE CULVERTS NOTES 1 & 2	STATEWIDE EXCEPT LOCATIONS SHOWN IN TABLE B	LOCATION SHOWN IN TABLE B	STATEWIDE EXCEPT LOCATIONS SHOWN IN TABLE B	LOCATION SHOWN IN TABLE B	STATEWIDE		
CONCRETE	V	V	V	V	V		
ALUMINUM COATED TYPE 2 CORRUGATED STEEL NOTE 3	V		V		V		
POLYMER COATED (10/10) CORRUGATED STEEL	V	V	V	V	V		
UNCOATED GALVANIZED CORRUGATED STEEL					V		
NOTES 3 & 4 GALVANIZED STEEL STRUCTURAL PLATE			V		V		
NOTE 3							
GALVANIZED STEEL STRUCTURAL PLATE WITH CONCRETE INVERT	V		V	V	V		
NOTE 3 CORRUGATED ALUMINUM ALLOY NOTE 3	V	V	V	V	V		
CORRUGATED ALUMINUM ALLOY STRUCTUAL PLATE	V	V	V	V	V		
NOTE 3							
POLYVINYLCHLORIDE (PVC) RIBBED PIPE (SMOOTH INTERIOR)	V	V	V	V	V		
POLYETHYLENE (PE) CORRUGATED TYPE C	V	V	V	V			
POLYETHYLENE (PE) CORRUGATED TYPE S	V	V	V	V	V		

NOTES:

1. ALLOWABLE TYPES OF PIPES FOR A SPECIFIC AREA ARE TO CONFORM TO THE CRITERIA SHOWN IN TABLES A, A1, B, AND C. ANY DEVIATION MUST BE APPROVED BY THE STATE LOCATION AND DESIGN ENGINEER AND THE DISTRICT MATERIALS ENGINEER.

2. SEE HEIGHT OF COVER TABLES FOR MINIMUM AND MAXIMUM COVER LIMITATIONS FOR EACH TYPE OF PIPE.

3. SEE TABLE C FOR MINIMUM AND MAXIMUM pH, RESISTIVITY, AND VELOCITY LIMITATIONS FOR METAL PIPES.

4. USE ONLY UNDER ENTRANCES WHERE THE PIPE SIZE IS LESS THAN OR EQUAL TO 30" DIAMETER (OR EQUIVALENT) AND THE HEIGHT OF COVER IS LESS THAN OR EQUAL TO 15' AND AS AN OUTLET PIPE FOR STANDARD DI-13 SHOULDER SLOT INLETS.

VDUT						
ROA	DA	ND	BRID	GE STANDARDS		
SHEET	17	OF	18	REVISION DATE		

107.21

SPECIFIC REFER	CATION
REFER	ENCE

CULVERT AND STORM SEWERS VIRGINIA DEPARTMENT OF TRANSPORTATION

ALLOWABLE PIPE CRITERIA FOR