



STANDARD	DIMENSIONS												
	A	B	C	D	E	F	G	H	I	J	K	M	N
JB-R1	18"	18"	19"	19"	20"	20"	21"	21"	24"	24"	4"	5/8"	1"
JB-R2	24"	24"	26"	26"	27"	27"	28"	28"	33"	33"	4"	5/8"	1"

NOTES:

THE COVER SHALL HAVE A NON-SKID SURFACE WITH LETTERS CAST IN THE DEPRESSION ON TOP. THE LETTERS "VDOT ELEC", "VDOT TRAFF", "VDOT COMM" OR "UTILITY" AS APPLICABLE ARE TO BE ONE (1) INCH WIDE AND RAISED ONE (1) INCH HIGH. COVERS USED FOR JUNCTION BOXES INSTALLED WITHIN MUNICIPALITIES SHALL NOT REQUIRE THE VDOT REFERENCE.

FOUR RECESSED 3/8" HEX BOLTS ARE REQUIRED FOR EACH COVER.

CASTINGS SHALL MEET ALL REQUIREMENTS OF AASHTO M306 AND AASHTO M105



ROAD AND BRIDGE STANDARDS

SHEET 2 OF 2

REVISION DATE

1317.11

**JUNCTION BOX
FOR TRAFFIC USE**

VIRGINIA DEPARTMENT OF TRANSPORTATION

SPECIFICATION
REFERENCE

700