



NOTES:

1. FOR MULTIPLE LINE INSTALLATIONS DIMENSION S IS TO GOVERN THE PROTECTION OUTSIDE THE CHANNEL WIDTH (W).
2. ON ANY SECONDARY ROADS INSTALLATION REQUIRING EROSION CONTROL STONE WHERE NO ENDWALL OR ENDSECTION IS SPECIFIED ON PLANS, CONSTRUCTION IS TO BE IN ACCORDANCE WITH DETAIL 2 SHOWN ABOVE.
3. GEOTEXTILE FABRIC TO BE INSTALLED UNDER ALL EROSION CONTROL STONE IN ACCORDANCE WITH THE SPECIFICATIONS.
4. S = DIAMETER OF CIRCULAR CULVERT OR SPAN FOR BOX, ELLIPTICAL OR ARCH CULVERT. H = DIAMETER OF CIRCULAR CULVERT OR RISE/HEIGHT FOR BOX, ELLIPTICAL OR ARCH CULVERT.
5. \*USE TYPICAL SECTION SHOWN ON PLANS OR FOR SIDESLOPE, BOTTOM WIDTH AND DEPTH OF CHANNEL, MATCH EXISTING DITCH OR NATURAL GROUND.

EC-1	MIN. DEPTH "D"
CLASS I	2'
CLASS II	3'

SPECIFICATION REFERENCE
204
245
303
414

STONE FOR EROSION CONTROL

VIRGINIA DEPARTMENT OF TRANSPORTATION