## Memorandum of Understanding VDEQ & VDOT Centralized Burning of Vegetative Debris from VDOT Roadside Maintenance Operations

## Table 1 - Siting Criteria

Siting Criterion	Vegetative Debris Storage	Vegetative Debris Burning	Ash*** Storage
Storage pile area not to exceed 1/3 acre	✓		<b>√</b>
Storage pile not to exceed 15' in height above base grade	√		<b>√</b>
Minimum of 50-foot firebreak (e.g., a clear zone absent of any structure or tree line, etc.) maintained between storage pile and any structure or tree line	<b>√</b>	√	✓
Minimum 50-foot setback from any property line	<b>V</b>		<b>√</b>
Minimum 100-foot setback from any regularly flowing surface water body, river, floodplain*, or wetland	√	√	√
Minimum 200-foot setback from water wells or other drinking water sources	<b>√</b>	√	√
Maximum 4:1 slope within the area of the vegetative debris; and within 50 feet of the vegetative debris	√	√	√
Minimum 300-foot setback from any roadway** or residential structure		<b>√</b>	

- \* VDOT and VDEQ agree that the floodplain (as it relates to this MOU) is defined by the edge of "bank full" condition which is generally referred to as the 2-year floodplain.
- \*\* Or as distant as practical provided no significant smoke is allowed to create deleterious driving conditions.
- \*\*\* Ash storage provisions also apply to incompletely burned vegetative debris.

12/5/2009 Page 8 of 10