
## NOTES:

- 1. THIS ITEM MAY BE PRECAST OR CAST IN PLACE.
- 2. CONCRETE TO BE CLASS A3 IF CAST IN PLACE, 4000 PSI IF PRECAST.
- 3. CURB HAVING A RADIUS OF 300 FEET OR LESS (ALONG FACE OF CURB) WILL BE PAID FOR AS
- 4. THE DEPTH OF CURB MAY BE REDUCED AS MUCH AS 3"
  (13" DEPTH) OR INCREASED AS MUCH AS 3" (19" DEPTH)
  IN ORDER THAT THE BOTTOM OF CURB WILL COINCIDE
  WITH THE TOP OF A COURSE OF THE PAVEMENT SUBSTRUCTURE.
  OTHERWISE THE DEPTH IS TO BE 16" AS SHOWN, NO ADJUSTMENT
  IN THE PRICE BID IS TO BE MADE FOR A DECREASE OR AN
  INCREASE IN DEPTH.
- 5. THIS CURB SHALL BE USED WHEN DESIGN SPEED IS GREATER THAN 40 MPH ON RURAL HIGHWAYS AND 45 MPH IN DEVELOPED URBAN AND SUBURBAN
- 6. WHEN THIS STANDARD IS TO BE TIED INTO EXISTING BARRIER CURB, THE TRANSITION IS TO BE MADE WITHIN 10' OR THE CHANGE IN STANDARDS MADE AT REGULAR OPENINGS.



STANDARD 4" CURB

VIRGINIA DEPARTMENT OF TRANSPORTATION

SPECIFICATION REFERENCE

105

502