

DESIGN FACTORS FOR A DESIGN SPEED OF 20 MPH (RURAL) USING E = 8% MAX.
DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)

DESIGN VELOCITY +20	DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)						DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)						DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)						DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)					
	1 @ 9'			1 @ 10'			1 @ 11'			1 @ 12'			2 @ 12'			16 FT			18 FT					
	Lt	Lr	w	Lt	Lr	w	Lt	Lr	w	Lt	Lr	w	Lt	Lr	w	Lt	Lr	w	Lt	Lr	w			
1800	NC	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
1213	2.0	59	2.0	28	0.0	30	0.0	33	0.0	33	0.0	33	33	0.0	49	0.0	39	0.0	49	0.0	39	39		
1148	2.1	57	59	2.1	28	0.0	30	32	0.0	33	35	0.0	49	52	0.0	39	40	0.0	49	52	0.0	39	41	
1090	2.2	54	59	2.1	28	0.0	30	33	0.0	33	36	0.0	49	54	0.0	39	42	0.0	49	54	0.0	39	41	
1036	2.3	52	59	2.1	28	0.0	30	35	0.0	33	38	0.0	49	56	0.0	39	44	0.0	49	56	0.0	39	41	
987	2.4	50	59	2.2	28	0.0	30	36	0.0	33	39	0.0	49	59	0.0	39	46	0.0	49	59	0.0	39	41	
941	2.5	48	59	2.2	28	0.0	30	38	0.0	33	41	0.0	49	61	0.0	39	48	0.0	49	61	0.0	39	41	
899	2.6	46	59	2.3	28	0.0	30	39	0.0	33	43	0.0	49	64	0.0	39	50	0.0	49	64	0.0	39	41	
860	2.7	44	59	2.3	28	0.0	30	41	0.0	33	44	0.0	49	66	0.0	39	52	0.0	49	66	0.0	39	41	
824	2.8	43	59	2.3	28	0.0	30	42	0.0	33	46	0.0	49	69	0.0	39	54	0.0	49	69	0.0	39	41	
790	2.9	41	59	2.4	28	0.0	30	44	0.0	33	48	0.0	49	71	0.0	39	56	0.0	49	71	0.0	39	41	
759	3.0	40	59	2.4	28	0.0	30	45	0.0	33	49	0.0	49	73	0.0	39	58	0.0	49	73	0.0	39	41	
729	3.1	39	59	2.5	28	0.0	30	47	0.0	33	51	0.0	49	76	0.0	39	60	0.0	49	76	0.0	39	41	
701	3.2	37	59	2.5	28	0.0	30	48	0.0	33	52	0.0	49	78	0.0	39	61	0.0	49	78	0.0	39	41	
674	3.3	36	59	2.5	28	0.0	30	50	0.0	33	54	0.0	49	81	0.0	39	63	0.0	49	81	0.0	39	41	
650	3.4	35	59	2.6	28	0.0	30	51	0.0	33	56	0.0	49	83	0.0	39	65	0.0	49	83	0.0	39	41	
626	3.5	34	59	2.6	28	0.0	30	53	0.0	33	57	0.0	49	86	0.0	39	67	0.0	49	86	0.0	39	41	
604	3.6	33	59	2.7	28	0.0	30	54	0.0	33	59	0.0	49	88	0.0	39	69	0.0	49	88	0.0	39	41	
582	3.7	32	59	2.7	28	0.0	30	55	0.0	33	60	0.0	49	90	0.0	39	71	0.0	49	90	0.0	39	41	
562	3.8	32	59	2.8	28	0.0	30	57	0.0	33	62	0.0	49	93	0.0	39	73	0.0	49	93	0.0	39	41	
543	3.9	31	59	2.8	28	0.0	30	58	0.0	33	64	0.0	49	95	0.0	39	75	0.0	49	95	0.0	39	41	
524	4.0	30	59	2.9	28	0.0	30	60	0.0	33	66	0.0	49	98	0.0	39	77	0.0	49	98	0.0	39	41	
506	4.1	29	59	2.9	28	0.0	30	61	0.0	33	67	0.0	49	100	0.0	39	79	0.0	49	100	0.0	39	41	
489	4.2	29	62	3.0	30	64	2.0	63	0.0	33	69	0.0	49	103	0.0	39	80	0.0	49	103	0.0	39	41	
473	4.3	29	63	3.0	30	66	2.0	66	0.0	33	72	0.0	49	105	0.0	39	82	0.0	49	105	0.0	39	41	
457	4.4	29	63	3.0	30	66	2.0	66	0.0	33	72	0.0	49	108	0.0	39	84	0.0	49	108	0.0	39	41	
442	4.5	29	65	3.1	31	68	2.1	68	0.0	33	73	0.0	49	110	0.0	39	86	0.0	49	110	0.0	39	41	
427	4.6	29	66	3.2	30	69	2.2	69	0.0	33	75	0.0	49	112	0.0	39	88	0.0	49	112	0.0	39	41	
413	4.7	29	68	3.2	31	71	2.2	70	0.0	33	77	0.0	49	115	0.0	39	90	0.0	49	115	0.0	39	41	
399	4.8	30	70	3.3	31	73	2.3	72	0.0	33	78	0.0	49	117	0.0	39	92	0.0	49	117	0.0	39	41	
385	4.9	29	71	3.3	31	74	2.3	73	0.0	33	80	0.0	49	120	0.0	39	94	0.0	49	120	0.0	39	41	
372	5.0	30	73	3.4	31	76	2.4	75	0.0	33	82	0.0	49	122	0.0	39	96	0.0	49	122	0.0	39	41	
358	5.1	30	75	3.5	31	78	2.5	76	0.0	33	83	0.0	49	125	0.0	39	98	0.0	49	125	0.0	39	41	
345	5.2	30	76	3.5	31	80	2.5	78	0.0	33	85	0.0	49	127	0.0	39	100	0.0	49	127	0.0	39	41	
332	5.3	30	78	3.6	31	81	2.6	79	0.0	33	86	0.0	49	129	0.0	39	101	0.0	49	129	0.0	39	41	
320	5.4	30	80	3.7	31	83	2.7	80	0.0	33	88	0.0	49	132	0.0	39	103	0.0	49	132	0.0	39	41	
308	5.5	30	82	3.8	31	85	2.8	82	0.0	33	90	0.0	49	134	0.0	39	105	0.0	49	134	0.0	39	41	
297	5.6	30	83	3.9	32	87	2.9	84	0.0	33	91	0.0	49	137	0.0	39	107	0.0	49	137	0.0	39	41	
286	5.7	30	85	3.9	32	89	2.9	85	0.0	33	93	0.0	49	139	0.0	39	109	0.0	49	139	0.0	39	41	
276	5.8	30	87	4.0	32	91	3.0	87	0.0	33	95	0.0	53	153	2.0	39	111	0.0	53	153	2.0	39	41	
266	5.9	31	89	4.1	32	93	3.1	89	0.0	33	97	0.0	54	157	2.2	39	113	0.0	54	157	2.2	39	41	
258	6.0	30	90	4.2	32	95	3.2	91	0.0	33	98	0.0	54	161	2.4	39	115	0.0	54	161	2.4	39	41	
248	6.1	31	92	4.3	32	97	3.3	93	0.0	33	99	0.0	55	165	2.6	39	117	0.0	55	165	2.6	39	41	
240	6.2	31	94	4.4	32	99	3.4	95	0.0	33	101	0.0	55	169	2.8	39	119	0.0	55	169	2.8	39	41	
232	6.3	31	96	4.5	33	101	3.5	97	0.0	33	103	0.0	55	173	3.0	39	120	0.0	55	173	3.0	39	41	
225	6.4	31	98	4.6	33	103	3.6	99	0.0	33	104	0.0	56	177	3.2	39	122	0.0	56	177	3.2	39	41	
217	6.5	31	100	4.7	33	105	3.7	101	0.0	33	106	0.0	56	181	3.4	39	124	0.0	56	181	3.4	39	41	
209	6.6	31	102	4.8	33	107	3.8	103	0.0	33	108	0.0	57	185	3.6	39	126	0.0	57	185	3.6	39	41	
202	6.7	32	104	4.9	33	109	3.9	105	0.0	33	109	0.0	57	189	3.8	39	128	0.0	57	189	3.8	39	41	
196	6.8	32	106	5.0	33	111	4.0	107	0.0	36	120	2.0	58	193	4.0	39	130	0.0	58	193	4.0	39	41	
189	6.9	32	108	5.1	33	113	4.1	109	0.0	36	122	2.1	58	198	4.2	39	132	0.0	58	198	4.2	39	41	
183	7.0	32	110	5.2	33	115	4.2	111	0.0	36	124	2.2	58	202	4.4	39	134	0.0	58	202	4.4	39	41	
176	7.1	32	112	5.3	33	117	4.3	113	0.0	36	127	2.3	59	206	4.6	39	136	0.0	59	206	4.6	39	41	
170	7.2	32	115	5.5	34	120	4.5	115	0.0	36	129	2.5	59	212	5.0	39	138	0.0	59	212	5.0	39	41	
164	7.3	33	117	5.6	34	122	4.6	117	0.0	37	132	2.6	60	217	5.2	39	140	0.0	60	217	5.2	39	41	
158	7.4	33	119	5.8	34	124	4.8	119	0.0	37	134	2.8	60	222	5.6	39	141	0.0	60	222	5.6	39	41	
152	7.5	33	122	5.9	34	127	4.9	121	0.0	37	137	2.9	61	227	5.8	39	143	0.0	61	227	5.8	39	41	
146	7.6	33	124	6.1	34	129	5.1	123	0.0	37	140	3.1	62	233	6.2	39	145	0.0	62	233	6.2	39	41	
139	7.7	33	127	6.3	35	132	5.3	125	0.0	38	143	3.3	63	239	6.6	39	147	0.0	63	239	6.6	39	41	
132	7.8	34	130	6.5	35	135	5.5	127	0.0	38	145	3.5	64	246	7.0	39	149	0.0	64	246	7.0	39	41	
124	7.9	34	133	6.8	35	138	5.8	129	0.0	38	149	3.8	65	254	7.6	39	151	0.0	65	254	7.6	39	41	
108	8.0	35	139	7.6	36	144	6.6	131	0.0	38	150	5.6	68	270	9.2	39	153	0.0	68	270	9.2	39	41	

NOTE: Lt, Lr & w VALUES IN FEET. LISTED RADIUS IS THE MINIMUM ALLOWABLE RADIUS FOR THE CORRESPONDING E, Lt, Lr, AND w VALUES.

SPECIFICATION REFERENCE

TRANSITION CURVES - RURAL
20 MPH DESIGN SPEED