2001 Road and Bridge Standards Volume 1 Table of Contents

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|-------------------|--------|---|---------|---------|---------|---------|
| EW-1 EW-1A | 101.01 | Standard Endwall for Pipe Culverts 12" - 36" Circular and 23" X 14" - 53" X 34" Elliptical Pipes | | | | |
| EW-1PC EW-1APC | 101.02 | Precast Endwall for Pipe Culverts 12" - 36" Circular and 23" X 14" - 53" X 34" Elliptical Pipes | | | | |
| | 101.03 | Standard Endwall for Pipe Culverts 42" - 96" Circular and 60" X 38" - 106" X 68" Elliptical Pipes | | | | |
| EW-2 EW-2A | 101.04 | Standard Endwall for Pipe Culverts 42" - 96" Circular Pipes | | | | |
| | 101.05 | Standard Endwall for Pipe Culverts 60" X 38" - 106" X 68" Elliptical Pipes | | | | |
| EW-2 PC | 101.06 | Precast Endwall for 42" - 96" Circular Pipe Culverts | | | | |
| EW-2A PC | 101.07 | Precast Endwall for 60" X 38" - 106" X 68" Elliptical Pipe Culverts | | | | |
| EW-2S | 101.08 | Standard Endwalls for 42"-96" Pipe Culverts 30 and 45 Degree Skews | | | | |
| 200 | 101.09 | Standard Endwalls for 42"-96" Pipe Culverts 30 and 45 Degree Skews | | | | |
| EW-2S PC | 101.10 | Precast Endwalls for Pipe Culverts | | | | |
| EW-6 | 101.11 | Endwalls for Multiple Pipe Culverts 12" - 36" Pipe | | | | |
| EW-6 PC | 101.12 | Precast Endwalls for Multiple Pipe Culverts | | | | |
| EW-6S | 101.13 | Endwalls for Multiple Pipe Culverts 12" - 36" Pipe 30 Degree Skew | | | | |
| EVV-03 | 101.14 | Endwalls for Multiple Pipe Culverts 12" - 36" Pipe 45 Degree Skew | | | | |
| EW-6S PC | 101.15 | Precast Endwalls for Multiple Pipe Culverts 12" - 36" Pipe 30 Degree Skew | | | | |
| | 101.16 | Precast Endwalls for Multiple Pipe Culverts 12" - 36" Pipe 45 Degree Skew | | | | |
| EW-7 | 101.17 | Endwalls for Multiple Pipe Culverts 42" - 96" Pipe | | | | |
| EW-7 PC | 101.18 | Precast Endwalls for Multiple Pipe Culverts 42" - 96" Pipe | | | | |
| EW-7S | 101.19 | Endwalls for Multiple Pipe Culverts 42" - 96" Pipe 30 Degree Skew | 7/01 | | | |
| 20070 | 101.20 | Endwalls for Multiple Pipe Culverts 42" - 96" Pipe 45 Degree Skew | | | | |
| EW-7S PC | 101.21 | Precast Endwalls for Multiple Pipe Culverts 42" - 96" Pipe 45 Degree Skew | | | | |
| EW-9 | 101.22 | Endwalls for Pipe Arches 13" - 38" Rise | | | | |
| EW-9 PC | 101.23 | Precast Endwalls for Pipe Arches 13" - 38" Rise | | | | |
| EW-10 | 101.24 | Endwalls for Multiple Pipe Arches 13" - 38" Rise | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|---------------------|--------|--|---------|---------|---------|---------|
| EW-10 PC | 101.25 | Precast Endwalls for Multiple Pipe Arches 13" - 38" Rise | | | | |
| | 101.26 | Pipe Endwall with Load-Carrying Grate for 12" - 60" Pipes | | | | |
| EW-11 | 101.27 | Pipe Endwall with Load-Carrying Grate for 12" - 60" Pipes | | | | |
| | 101.28 | Pipe Endwall with Load-Carrying Grate for 12" - 60" Pipes | | | | |
| EW-11A | 101.29 | Pipe Endwall with Load - Carrying Grate for 12" - 24" Pipes | | | | |
| | 101.30 | Pipe Endwall with Load - Carrying Grate for 12" - 24" Pipes | | | | |
| EW-11A PC | 101.31 | Precast Pipe Endwall with Load-Carrying Pipe Grate for 12" - 24" Pipes | | | | |
| EW-12 | 101.32 | Endwalls for Pipe Underdrain | 7/03 | 7/04 | | |
| ES-1 | 102.01 | Flared End-Section for Concrete Pipe Culverts (12"-60") | 7/01 | | | |
| ES-1A | 102.02 | Flared End-Section for 23" X 14" to 53" X 34" Elliptical Concrete Pipe Culverts | 7/01 | | | |
| ES-2 | 102.03 | Flared End-Section for 12" - 60" Corrugated Pipe Culverts | 7/01 | | | |
| ES-3 | 102.04 | Flared End-Section for Metal Pipe Arches 13" - 47" Rise | | | | |
| | 103.01 | Precast Unit Assembly Diagram | | | | |
| | 103.02 | Legend & General Notes - Precast | | | | |
| T-DI-1 | 103.03 | Precast Top Unit - DI-1 | | | | |
| T-DI-2 | 103.04 | Precast Top Unit - DI-2 | 3/03 | | | |
| T-DI-3, 4 | 103.05 | Precast Top Unit - DI-3, DI-4 | 3/03 | | | |
| T DI 0, 4 | 103.06 | Precast Top Unit - DI-3, DI-4 | | | | |
| T-DI-5 | 103.07 | Precast Top Unit - DI-5 | | | | |
| T-DI-7 | 103.08 | Precast Top Unit - DI-7 | | | | |
| T-MH-2 | 103.09 | Precast Manhole Top Units | | | | |
| R-1, 2, 3 | 103.10 | Precast Reducer and Riser Units | | | | |
| B-1, 2 | 103.11 | Precast Base Units | | | | |
| B-3 | 103.12 | Precast Base Unit | | | | |
| B-4 | 103.13 | Corrugated Metal Base Unit | | | | |
| DI-1 | 104.01 | Standard Drop Inlet 12"-24" Pipe: Maximum Depth (H) = 10' | | | | |
| DI-1A | 104.02 | Standard Drop Inlet 12"-24" Pipe: Depth (H) 10' to 20' | 7/04 | | | |
| DI-2A, 2B, | 104.03 | Standard Curb Drop Inlet 12"-24" Pipe: Maximum Depth (H) = 9' | | | | |
| 2C | 104.04 | Dimensions & Quantities | 1/04 | | | |
| DI-2AA, 2BB, 2CC | 104.05 | Standard Curb Drop Inlet 12"-24" Pipe: Depth (H) = 9' to 20' | | | | |
| DI-2D, 2E, | 104.06 | Standard Curb Drop Inlet 30"-48" Pipe: Maximum Depth (H) = 9' | 1/04 | | | |
| 2F | 104.07 | Dimensions & Quantities | | | | |
| DI-2DD, 2EE, 2FF | 104.08 | Standard Curb Drop Inlet 30"-48" Pipe: Depth (H) = 9' to 20' | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------------------------|--------|---|---------|---------|---------|---------|
| DI-3A, 3B, | 104.09 | Standard Curb Drop Inlet 12"-30" Pipe: Maximum Depth (H) = 8' | | | | |
| 3C | 104.10 | Dimensions & Quantities | | | | |
| DI-3AA, 3BB, 3CC | 104.11 | Standard Curb Drop Inlet 12"-30" Pipe: Depth (H) 8' to 20' | | | | |
| DI-3D, 3E, 3F | 104.12 | Standard Curb Drop Inlet (With Utility Space) 12"-30" Pipe: Maximum Depth (H) = 8' | 7/01 | 7/02 | | |
| 51 | 104.13 | Dimensions & Quantities | | | | |
| DI-3DD, 3EE, 3FF | 104.14 | Standard Curb Drop Inlet (With Utility Space) 12"-30" Pipe: Depth (H) = 8' to 20' | | | | |
| DI-4A, 4B, | 104.15 | Standard Curb Drop Inlet 36"-48" Pipe: Maximum Depth (H) = 8' | | | | |
| 4C | 104.16 | Dimensions & Quantities | | | | |
| DI-4AA DI-3BB DI-4CC | 104.17 | Standard Curb Drop Inlet 36"-48" Pipe: Depth (H) 8' to 20' | | | | |
| DI-400 DI-4D DI-4E | 104.18 | Standard Curb Drop Inlet (With Utility Space) 36"-48" Pipe: Maximum Depth (H) = 8' | | | | |
| DI-4F | 104.19 | Dimensions & Quantities | | | | |
| DI-4DD, 4EE, 4FF | 104.20 | Standard Curb Drop Inlet (With Utility Space) 36"-48" Pipe: Depth (H) 8' to 16' | | | | |
| DI-5 | 104.21 | Standard Ditch Drop Inlet | | | | |
| | 104.22 | Standard Median Drop Inlet 12"-42" Pipe | | | | |
| DI-7, 7A , | 104.23 | Cover & Gutter Details | | | | |
| 7B | 104.24 | Standard DI-7, 7A or 7B with Flume Connection 12" to 36" Pipe | | | | |
| DI-9 | 104.25 | 15" Pipe Tee Section Drop Inlet | 7/04 | | | |
| DI-10G, | 104.26 | Concrete Median Barrier Drop Inlet | | | | |
| 10H, 10I | 104.27 | Quantities & Dimensions | | | | |
| DI-10J, | 104.28 | Concrete Median Barrier Drop Inlet | | | | |
| 10K, 10L | 104.29 | Concrete Median Barrier Drop Inlet | 7/01 | 7/02 | | |
| | 104.30 | Multigrate Drop Inlet for Pipe Sizes 12"-72" | | | | |
| DI-12, 12A | 104.31 | Grate Details | | | | |
| | 104.32 | Quantities & Dimension | | | | |
| DI-12B, | 104.33 | Multigrate Drop Inlet for Pipe Sizes 12"-36" | | | | |
| 12C | 104.34 | Grate Details & Quantities | | | | |
| DI-13 | 104.35 | Shoulder Slot Inlet | | | | |
| DI 10 | 104.36 | Shoulder Slot Inlet | | | | |
| PI-1 | 104.37 | Method of Outlet Pipe Installation for DI-13 | | | | |
| DI-14A, | 104.38 | Concrete Median Barrier Drop Inlet (Tall Wall) | | | | |
| 14B, 14C | 104.39 | Quantities & Dimensions | | | | |
| DI-14D, | 104.40 | Concrete Median Barrier Drop Inlet (Tall Wall) | 7/01 | | | |
| 14E, 14F | 104.41 | Concrete Median Barrier Drop Inlet (Tall Wall) | 7/01 | | | |
| DI-MB | 104.42 | Concrete Masonry Block Curb Drop Inlet | | | | |
| IC-2 | 105.01 | Standard Inlet Frame and Cover | | | | |
| 10-2 | 105.02 | Standard Inlet Frame and Cover | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|-------------|--------|---|----------|---------|---------|---------|
| IC-2 | 105.03 | Precast Inlet and Frame Cover | | | | |
| | 106.01 | Manhole for 12" to 48" Pipe Culvert | 7/01 | | | |
| | 106.02 | Standard Manhole Frame and Cover | | | | |
| MH-1 | 106.03 | Standard Manhole Frame and Cover | | | | |
| | 106.04 | Standard Manhole Frame and Cover | 7/02 | | | |
| | 106.05 | Standard Manhole Frame and Cover | | | | |
| MH-1A | 106.06 | Standard Manhole Frame and Cover | | | | |
| MH-2 | 106.07 | Precast Manhole | | | | |
| IS-1 | 106.08 | Method of Shaping Manhole and Inlet Culverts | | | | |
| ST-1 | 106.09 | Standard Step | | | | |
| | 106.10 | Junction Box Chamber Details for 48" - 72" Pipe Culverts | | | | |
| JB-1 | 106.11 | Junction Box Details for Angular Connections of 48" - 72" Pipe Culverts | | | | |
| 021 | 106.12 | Junction Box Tower Details for 48" - 72" Pipe Culverts | | | | |
| | 106.13 | Junction Box Displacement Quantities for 48" - 72" Pipe Culverts | | | | |
| SL-1 | 106.14 | Typical Concrete Safety Slab for Drop Inlets, Manholes & Junction Boxes | | | | |
| | 107.00 | Installation of Pipe Culverts and Storm Sewers Circular Pipe Bedding and Backfill - Notes | New 1/04 | | | |
| | 107.01 | Installation of Pipe Culverts and Storm Sewers Circular Pipe Bedding and Backfill - Method "A" Installation of Pipe Culverts and Storm Sewers | 1/04 | | | |
| PB-1 | 107.02 | Elliptical Pipe Bedding and Backfill - Method "A" | 1/04 | 7/04 | | |
| | 107.03 | Installation of Pipe Culverts and Storm Sewers Pipe Arch Bedding and Backfill | 1/04 | | | |
| | 107.04 | Installation of Box Culvert Bedding and Backfill Method "A" | 1/04 | | | |
| | 107.05 | Concrete Pipe - Class Table for H-20 Live Load | | | | |
| | 107.06 | Elliptical Concrete Pipe - Table for H-20 Live | | | | |
| | 107.07 | Corrugated Steel Pipe - Height of Cover Table for H-20 Live Load | | | | |
| | 107.08 | Corrugated Aluminum Alloy Pipe - Height of Cover Table for H-20 Live Load | | | | |
| DO 1 | 107.09 | Corrugated Aluminum Alloy Pipe - Height of Cover Table for H-20 Live Load | | | | |
| PC-1 | 107.10 | Corrugated Steel Pipe Arch - Height of Cover Table for H-20 Live Load | | | | |
| | 107.11 | Corrugated Aluminum Alloy Pipe Arch - Height of Cover Table for H-20 Live Load | | | | |
| | 107.12 | Structural Plate Steel Pipe - Height of Cover Table for H-20 Live Load | | | | |
| | 107.13 | Structural Plate Aluminum Alloy Pipe - Height of Cover Table for H-20 Live Load | | | | |
| | 107.14 | Structural Plate Steel Pipe Arch- Height of Cover Tables for H-20 Live Load | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------------|---------|---|----------|---------|---------|---------|
| | 107.15 | Structural Plate Steel Pipe Arch - Height of Cover Table for H-20 Live Load | | | | |
| | 107.16 | Structural Plate Aluminum Alloy Pipe Arch - Height of Cover Table for H-20 Live Load | | | | |
| | 107.17 | Aluminum Spiral Rib Pipe - Height of Cover Table for H-20 Live Load | | | | |
| PC-1 | 107.18 | Steel Spiral Rib Pipe - Height of Cover Table for H-20 Live Load | | | | |
| | 107.19 | Cast Iron Pipe - Strength Table for H-20 Live Load | | | | |
| | 107.20 | Vitrified Clay and Plastic Pipe - Maximum Cover Table for H-20 Live Load | 7/01 | | | |
| | 107.21 | Shop Elongation of Metal Pipes and Structural Plate Pipe | | | | |
| PP-1 | 107.22 | Details for Backfilling Abandoned Culverts | | | | |
| UD-1 | 108.01 | Standard Groundwater Underdrain | 7/03 | | | |
| UD-2 | 108.02 | Pipe Underdrain for Use with Raised Grass Median Strips | 7/03 | | | |
| UD-3 | 108.03 | Standard Sidewalk Underdrain | 7/03 | | | |
| CD-1 | 108.04 | Standard Combination Underdrains (at Lower End of Cuts) | 7/03 | | | |
| CD-2 | 108.05 | Standard Combination Underdrains (at Grade Sags and Bridge Approaches) | 7/03 | | | |
| UD-4 | 108.06 | Standard Pavement Edgedrain | 7/03 | 1/04 | | |
| UD-4 | 108.07 | Standard Pavement Edgedrain | 7/03 | | | |
| UD-5 | 108.08 | Prefabricated Geocomposite Retrofit Pavement Edgedrain | | | | |
| UD-7 | 108.09 | Standard Retrofit Edgedrain | 7/03 | | | |
| PG-2A | 109.01 | Standard Paved Ditches | 7/02 | 7/04 | | |
| PG-3 | 109.01a | Standard Rip Rap Ditch and Slope Protection | New 7/03 | | | |
| PG-4 | 109.02 | Standard Paved Flume for 12" - 24" Pipe Culverts | | | | |
| PG-5 | 109.03 | Standard Paved Ditches | | | | |
| PG-6A, 6B | 109.04 | Standard Precast Paved Ditches | | | | |
| PG-7 | 109.05 | Ditch Flume Connector | 7/02 | | | |
| SB-1 | 110.01 | Standard Spring Box | 7/01 | 3/03 | | |
| SB-1 PC | 110.02 | Precast Spring Box | 7/01 | 3/03 | | |
| EG-1, 1A | 111.01 | Standard Energy Dissipator for use with Paved Flume | | 0,00 | | |
| EG-1, 1A PC | 111.02 | Precast Energy Dissipator | | | | |
| PS-2 | 112.01 | Standard Pipe Spillout for 12"-18" Pipe Culverts | | | | |
| PS-3 | 112.02 | Standard Pipe Spillout for 21"-30" Pipe Culverts | | | | |
| TD-CL | 113.01 | Temporary Diversion Channel & Acceptable Linings | | | | |
| EC-1 | 114.01 | Stone for Erosion Control | | | | |
| EC-2 | 114.02 | Protective Covering Installation Criteria | | | | |
| EC-3 | 114.03 | Soil Stabilization Criteria | | | | |
| EC-3 | 114.04 | Soil Stabilization Mat Slope Installation | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|-----------|---------|---------|---------|
| EC-4 | 114.05 | Rock Check Dams Type I & II | | | | |
| EC-5 | 114.06 | Temporary Silt Fence and Filter Barrier | 3/03 | | | |
| EC-6 | 114.07 | Drop Inlet Silt Trap (Type A and B) | 7/01 | 3/03 | | |
| EC-7 | 114.08 | Typical Sediment Trap | | | | |
| EC-8 | 114.09 | Dewatering Basin | | | | |
| EC-9 | 114.10 | Temporary Diversion Dike | | | | |
| | 115.01 | Temporary Erosion & Siltation Control | 3/03 | 1/04 | 7/04 | |
| ESC-INS | 115.02 | Temporary Erosion & Siltation Control | | | | |
| | 115.03 | Temporary Erosion & Siltation Control | | | | |
| | 116.01 | Cast-In-Place Stormwater Management Drainage Structure | 3/03 | | | |
| SWM-1 | 116.02 | Precast Stormwater Management Drainage Structure | 3/03 | | | |
| | 116.03 | Stormwater Management Drainage Structure (SWM) Details | VOID 3/03 | | | |
| | 116.04 | Stormwater Management (SWM) Details | 3/03 | | | |
| | 116.05 | Stormwater Management (SWM) Details | 3/03 | | | |
| SWM-DR | 116.06 | Stormwater Management (SWM) Details | 3/03 | | | |
| | 116.07 | Stormwater Management (SWM) Details | New 3/03 | | | |
| | 116.08 | Stormwater Management (SWM) Details | New 3/03 | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|-----------|--------|--|---------|---------|---------|---------|
| CG-2 | 201.01 | Standard 6" Curb | | | | |
| CG-3 | 201.02 | Standard 4" Curb | | | | |
| CG-6 | 201.03 | 6" Combination Curb & Gutter | | | | |
| CG-7 | 201.04 | 4" Combination Curb & Gutter | | | | |
| MC-3, 3A | 201.05 | Asphalt Concrete Curb and Median for Temporary or Permanent Installation | | | | |
| MC-3B, 3C | 201.06 | Asphalt Concrete Curb and Median for Temporary or Permanent Installation | | | | |
| | 201.07 | Asphalt Curb and Gutter and Asphalt Paving Under Guardrail | | | | |
| MC-4 | 201.08 | Asphalt Curb and Gutter and Asphalt Paving Under Guardrail | | | | |
| MC-1 | 202.01 | Concrete Median Curb | | | | |
| MS-1 | 202.02 | Standard Solid Concrete Raised Median Strip | 7/04 | | | |
| MS-1A | 202.03 | Standard Solid Concrete Raised Median Strip | 7/01 | 7/04 | | |
| MS-2 | 202.04 | Standard Raised Grass Median Strips | | | | |
| MS-4 | 202.05 | Standard Raised Asphalt Median with P.C. Concrete Curb | | | | |
| CG-9A | 203.01 | Standard Entrance Gutter with Flared Opening for Use Across Sidewalk | | | | |
| CG-9B | 203.02 | Standard Entrance Gutter For Use With Unpaved Space Between Curb & Gutter | 1/04 | | | |
| CG-9D | 203.03 | Standard Entrance Gutter | 1/04 | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|---------|---------|---------|---------|
| CG-11 | 203.04 | Method of Treatment - Connection for Street Intersections and Commercial Entrances | 7/01 | | | |
| CG-12A | 203.05 | Perpendicular Curb Ramp (Access for Mobility Impairments) | 7/01 | 3/03 | 1/04 | |
| CG-12B | 203.06 | Parallel Curb Ramp (Access for Mobility Impairments) | 3/03 | 1/04 | 7/04 | |
| CG-12C | 203.07 | Combination (Parallel & Perpendicular) Curb Ramp (Access for Mobility Impairments) | 7/01 | 3/03 | 1/04 | 7/04 |
| CG-13 | 203.08 | Commercial Entrance (Heavy Truck Traffic) | 3/03 | 1/04 | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|--|---------|---------|---------|---------|
| | 301.01 | Plain and Reinforced Concrete Pavement Showing Reinforcement, Longitudinal and Transverse Joints | 7/02 | | | |
| | 301.02 | Plain and Reinforced Concrete Pavement Showing Reinforcement, Longitudinal and Transverse Joints | 7/03 | | | |
| PR-2 | 301.03 | Plain and Reinforced Concrete Pavement Showing Reinforcement, Longitudinal and Transverse Joints | 7/03 | | | |
| | 301.04 | Standard Load Transfer Assembly Contraction Joint | | | | |
| | 301.05 | Standard Load Transfer Assembly Expansion Joint | | | | |
| | 301.06 | 8" Continuously Reinforced Concrete Pavement (Wire Mesh Reinforcement) | | | | |
| | 301.07 | 8" Continuously Reinforced Concrete Pavement (Steel Bar Reinforcement) | | | | |
| PR-3 | 301.08 | 8" Continuously Reinforced Concrete Pavement (for use with Bar or Wire Mesh Reinforcement) | | | | |
| | 301.09 | 8" Continuously Reinforced Concrete Pavement (Leave out Joint Detail) | | | | |
| | 301.10 | 9" Continuously Reinforced Concrete Pavement (Steel Bar Reinforcement) | | | | |
| PR-4 | 301.11 | 9" Continuously Reinforced Concrete Pavement (for use with Bar Reinforcement only) | | | | |
| | 301.12 | 9" Continuously Reinforced Concrete Pavement (Leave Out Joint Detail) | | | | |
| PR-5 | 301.13 | 9" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|-----------|---------|---------|---------|
| PR-5 | 301.14 | 9" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | 1/04 | | |
| FR-5 | 301.15 | 9" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| | 301.16 | 10" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| PR-6 | 301.17 | 10" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | 1/04 | | |
| | 301.18 | 10" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| | 301.19 | 11" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| PR-7 | 301.20 | 11" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | 1/04 | | |
| | 301.21 | 11" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| | 301.22 | 12" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| PR-8 | 301.23 | 12" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | 1/04 | | |
| | 301.24 | 12" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| | 301.25 | 13" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| PR-9 | 301.26 | 13" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | 1/04 | | |
| | 301.27 | 13" Continuously Reinforced Concrete Pavement 14 Foot Travel Lane | 7/03 | | | |
| XJ-1 | 302.01 | Bridge Approach Expansion Joint (for Widening or Maintenance of Existing XJ-1 Only) | | | | |
| | 302.02 | Bridge Approach Expansion Joint (Installation Criteria) | | | | |
| WP-1 | 303.01 | Method of Widening Pavement at Bridge Approaches | | | | |
| RS-1 | 304.01 | Rumble Strips (Asphalt Shoulder) | 3/03 | | | |
| RS-2 | 304.02 | Rumble Strips (Concrete Shoulder) | VOID 3/03 | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|---------|---------|---------|---------|
| RW-2 | | Concrete Gravity Retaining Walls - Level Backfill | | | | |
| RW-3 | 401.02 | Concrete Gravity Retaining Walls Infinite Surcharge and Deck Surcharge -Loaded | 7/01 | 7/02 | 7/04 | |
| RW-2,3 | | Suggested Rustication Treatments for Retaining Walls | | | | |
| | 402.01 | Standard Reinforcing Concrete Crib Wall | | | | |
| CW-1 | 402.02 | Standard Reinforcing Concrete Crib Wall | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|-----------------|--------|--|---------|-----------|---------|---------|
| | 501.01 | Standard Guardrail Hardware | | | | |
| GR-HDW | 501.02 | Standard Guardrail Hardware | | | | |
| | 501.03 | Standard Guardrail Hardware | | | | |
| | 501.04 | Standard Blocked-Out W Beam Guardrail (Strong Post) | | | | |
| GR-2, 2A | 501.05 | Standard Blocked-Out W Beam Guardrail (Strong Post) | 7/01 | 7/03 | | |
| | 501.06 | Cable Guardrails | 7/03 | 7/04 | | |
| GR-3 | 501.07 | Cable Guardrails | | | | |
| | 501.08 | Cable Guardrails | 7/04 | | | |
| GR-6 | 501.09 | Terminal Treatment for W Beam Guardrail | 7/01 | 7/02 | 7/03 | |
| GK-0 | 501.10 | Terminal Treatment for W Beam Guardrail | 7/01 | 3/03 | 7/03 | 7/04 |
| | 501.11 | Breakaway Cable Terminal - 4' Flare | 7/02 | 7/03 | 7/04 | |
| GR-7 | 501.12 | Breakaway Cable Terminal - 4' Flare | 7/02 | VOID 7/04 | | |
| | 501.13 | Breakaway Cable Terminal - 4' Flare | 7/04 | | | |
| GR-8, 8A, | 501.14 | Standard W Beam Guardrail (Weak Post System) | 7/01 | 7/03 | | |
| 8B, 8C | 501.15 | Standard W Beam Guardrail (Weak Post System) | 7/01 | 1/04 | | |
| GR-SP | 501.16 | Guardrail Terminal Installation Site Preparation Requirements for GR-7 | 7/01 | 7/04 | | |
| | 501.17 | Guardrail Terminal Installation Site Preparation Requirements for GR-9 | 7/01 | | | |
| GR-9 | 501.18 | Alternate Breakaway Cable Terminal - No Flare | 7/02 | 7/03 | 7/04 | |
| GR-10 | 501.19 | Guardrail at Low-Fill Culvert | 1/04 | | | |
| | 501.20 | Guardrail at Low-Fill Culvert | 1/04 | | | |
| GR-11 | 501.21 | Trailing End Terminal Treatment | 7/02 | 3/03 | 7/03 | |
| | 501.22 | Standard Box Culvert Guardrail (Texas T-6) | | | | |
| BGR-01 | 501.23 | Standard Box Culvert Guardrail (Texas T-6) | | | | |
| | 501.24 | Standard Box Culvert Guardrail (Texas T-6) | | | | |
| | 501.25 | W Beam Guardrail-Fixed Object Attachment For Use With Vertical Fixed Objects and Guardrail (Wood Posts) | 7/01 | | | |
| GR-FOA-1 | 501.26 | W Beam Guardrail-Fixed Object Attachment For Use With Vertical Fixed Objects and Guardrail (Steel Posts) | 7/01 | | | |
| | 501.27 | W Beam Guardrail-Fixed Object Attachment Rubrail and Hardware Details | 7/01 | | | |
| GR-FOA-2 | 501.28 | W Beam Guardrail-Fixed Object Attachment For Use Between Safety Shape and Guardrail (Wood Posts) | 7/01 | | | |
| | 501.29 | W Beam Guardrail-Fixed Object Attachment For Use Between Safety Shape - Steel Posts | 7/01 | | | |
| GR-FOA-2 & 4 | 501.30 | W Beam Guardrail-Fixed Object Attachment Rubrail and Hardware Details | 7/01 | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|------------------|--------|---|---------|---------|---------|---------|
| GR-FOA-4 | 501.31 | Blocked-Out W-Beam Median Barrier - Fixed Object Attachment For Use Between MB-7 & MB-3 | | | | |
| GR-FOA-4 | 501.32 | Blocked-Out W-Beam Median Barrier - Fixed Object Attachment Rubrail and Hardware Details | | | | |
| | 501.33 | W Beam Guardrail Installation Criteria (At Bridge Piers) | 7/02 | 3/03 | | |
| | 501.34 | W Beam Guardrail Installation Criteria (At Dual Bridges) | 7/01 | 3/03 | | |
| | 501.35 | W Beam Guardrail Installation Criteria | | | | |
| GR-INS | 501.36 | W Beam Guardrail Installation Criteria | | | | |
| | 501.37 | W Beam Guardrail Installation Criteria | | | | |
| | 501.38 | W Beam Guardrail Installation Criteria | 7/03 | | | |
| | 501.39 | W Beam Guardrail Installation Criteria | 7/01 | 1/04 | | |
| | 501.40 | W Beam Guardrail and Median Barrier Installation Criteria | 7/01 | | | |
| MB-3 | 501.41 | Blocked-Out W Beam Median Barrier | 1/04 | | | |
| | 501.42 | Standard W Beam Median Barrier (Weak Post System) | 7/01 | 7/03 | | |
| MB-5 | 501.43 | Standard W Beam Median Barrier (Weak Post System) | | | | |
| MB-7D, 7E, 7F | 501.44 | Concrete Median Barrier | 1/04 | | | |
| | 501.45 | Precast Traffic Barrier Concrete Service | 1/04 | | | |
| MB-7D PC | 501.46 | Precast Traffic Barrier Concrete Service | | | | |
| | 501.47 | Concrete Median Barrier with F Shape Type I, II, or III | 1/04 | | | |
| MB-8A | 501.48 | Concrete Median Barrier with F Shape Type I, II, or III | | | | |
| MB-9A | 501.49 | Cast In Place Concrete Median Barrier 12 Foot Terminal Section | | | | |
| MB-9A PC | 501.50 | Precast Concrete Median Barrier 12 Foot Terminal Section | | | | |
| | 501.51 | Traffic Barrier Service Concrete Parapet (Single Face) (For Temporary Installation on Bridge Deck Exterior) | 7/02 | | | |
| MB-10A | 501.52 | Traffic Barrier Service Concrete Parapet (Single Face) (For Temporary Installation on Bridge Deck Exterior) | 7/02 | | | |
| | 501.53 | Traffic Barrier Service Concrete Parapet (Double Face) (For Temporary Installation on Bridge Deck Exterior) | | | | |
| MB-11A | 501.54 | Traffic Barrier Service Concrete Parapet (Double Face) (For Temporary Installation on Bridge Deck Exterior) | | | | |
| MB-12A, B, | 501.55 | Concrete Median Barrier (Tall Wall) | 7/04 | | | |
| C | 501.56 | Concrete Median Barrier (Tall Wall) | 1/04 | | | |
| MB-13 | 501.57 | Concrete Median Barrier Type I, II, or III | | 1 | | 1 |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|-----------|--------|---|---------|---------|---------|---------|
| MB-13 | 501.58 | Concrete Median Barrier Type I, II, or III | 1/04 | | | |
| | 501.59 | Precast Concrete Median Barrier Positive Connection Options | | | | |
| | 501.60 | Precast Concrete Median Barrier Positive Connection Options | | | | |
| MB-INS | 501.61 | Precast Concrete Median Barrier Positive Connection Options | | | | |
| | 501.62 | Butting Traffic Barrier Service to Single Face Parapet Service | 7/02 | | | |
| | 501.63 | Butting Traffic Barrier Service to Single Face Parapet Service | 7/02 | | | |
| FOA-CZ | 501.64 | W-Beam Guardrail Installation Criteria Fixed Object Attachment Methods For Construction Zones | | | | |
| FE | 502.01 | Standard Fence General Notes | | | | |
| FE-W1, W2 | 502.02 | Standard Fence Woven Wire Fabric | 7/04 | | | |
| FE-B | 502.03 | Standard Fence Barbed Wire | 7/04 | | | |
| FE-CL | 502.04 | Standard Fence Chain Link | 7/03 | 1/04 | 7/04 | |
| FE-G | 502.05 | Standard Fence Gates | | | | |
| FE-4 | 502.06 | Water Gates in Fence Lines | | | | |
| FE-6 | 502.07 | Standard Method of Fence Grounding | 1/04 | 7/04 | | |
| RM-1 | 503.01 | Standard Plan and Method of Setting Right of Way Monuments | | | | |
| RM-2 | 503.02 | Standard Plan and Method of Setting Right of Way Monuments | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|----------|---------|---------|---------|
| S-1 | 601.01 | Standard Concrete Steps for 1½ : 1 Slopes | 7/02 | | | |
| 5-1 | 601.02 | Standard Concrete Steps for 1½: 1 Slopes | | | | |
| S-2 | 601.03 | Standard Concrete Steps for 2: 1 Slopes | 7/02 | | | |
| 5-2 | 601.04 | Standard Concrete Steps for 2: 1 Slopes | | | | |
| HR-1 | 601.05 | Standard Handrail Method of Locating and Erecting | 7/04 | | | |
| LR-1 | 601.06 | Minimum Design for Small Boat Launching Ramps at Public Landings | | | | |
| SP-1 | 601.07 | Settlement Plate | | | | |
| SI-1,2,3 | 602.01 | Standard Plan for Sign Islands | | | | |
| PE-1 | 602.02 | Standard Private Entrances | | | | |
| CR-1 | 602.03 | Standard Maintenance Crossover for use on Freeways | | | | |
| RFD-1 | 603.01 | Standard Mailbox | 7/03 | 7/04 | | |
| RFD-1 | 603.02 | Standard Mailbox | New 7/03 | 1/04 | 7/04 | |
| G-3 | 604.01 | Precast Concrete Cattle Guard | | | | |
| G-3A | 604.02 | Precast Concrete Cattle Guard | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|-----------|---------|---------|---------|
| NG-1 | 605.01 | Storage Facility for Nuclear Gauge | | | | |
| RU-1 | 606.01 | Methods of Undercutting Rock | | | | |
| SS-1 | 607.01 | Standard Method of Setting and Marking Slope Stakes | | | | |
| SD-1 | 608.01 | Sight Distances on Horizontal Curves Height of Eye 3.5 Feet; Height of Object 0.5 and 4.25 Feet | | | | |
| SD-2 | 608.02 | Sight Distance on Vertical Curves | | | | |
| 50-2 | 608.03 | Sight Distance on Vertical Curves | | | | |
| SD-3 | 608.04 | Sight Distance on Vertical Curves | | | | |
| 30-3 | 608.05 | Sight Distance on Vertical Curves | | | | |
| SD-4 | 608.06 | Sight Distance on Vertical Curves | New 10/02 | | | |
| 50-4 | 608.07 | Sight Distance on Vertical Curves | New 10/02 | | | |
| SD-5 | 608.08 | Sight Distance on Vertical Curves | New 10/02 | | | |
| 50-5 | 608.09 | Sight Distance on Vertical Curves | New 10/02 | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|--|---------|---------|---------|---------|
| CS-1, 1A | 701.00 | Typical Methods of Grading Side Slopes | | | | |
| CS-2 | 701.01 | Suggested Drainage Treatment at Beginning of Fills | | | | |
| CS-2A | 701.02 | Typical Methods of Grading Side Slopes | | | | |
| CS-3 | 701.03 | Typical Methods of Grading Side Slopes | | | | |
| CS-3A | 701.04 | Typical Methods of Grading Side Slopes | | | | |
| CS-3B | 701.05 | Typical Methods of Grading Side Slopes | | | | |
| CS-4 | 701.06 | Typical Methods of Grading Side Slopes | | | | |
| CS-4A | 701.07 | Typical Methods of Grading Side Slopes | | | | |
| CS-4B | 701.08 | Typical Methods of Grading Side Slopes | | | | |
| CS-4C | 701.09 | Typical Methods of Grading Side Slopes | | | | |
| CS-4E | 701.10 | Typical Methods of Grading Side Slopes | | | | |
| GS-10 | 702.00 | Minimum Design Criteria for Temporary Detour (Maintenance of Traffic) | 3/03 | | | |
| GS-11 | 702.01 | Standard Shoulder Design for All Systems Except Local Roads and Streets | 7/01 | 3/03 | | |
| GS-12 | 702.02 | Standard Shoulder Designs for Local Roads and Streets | 3/03 | | | |
| GS-13 | 702.03 | Standard Graded Median Designs | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|--|---------|---------|---------|---------|
| | 801.01 | Transition Curves for Rural and Urban | | | | |
| | | Highways and Street Conditions | | | | |
| | 801.02 | Explanation of Tables and Instructions for use - Urban Condition | | | | |
| | | Explanation of Tables and Instructions for use | | | | |
| | 801.03 | - Rural Condition | | | | |
| | 801.04 | Explanation of Tables and Instructions for use - General Condition | | | | |
| | 801.05 | Details for Transitioned Baseline Rural Condition With Pavement Widening | | | | |
| | 801.06 | Details for Non-Transitioned Baseline Urban Conditions and Rural Condition Without Pavement Widening | | | | |
| | 801.07 | Details of Superelevation About Baseline | | | | |
| | | Details of Superelevation About Baseline | | | | |
| | 801.08 | | | | | |
| | 801.09 | Example for Four Lane Roadways | | | | |
| | 801.10 | Cross Section - Four Lane Roadway | | | | |
| | 801.11 | Method of Applying TC-5 on Compound and Reverse Curves Rural Condition Only With Pavement Widening | | | | |
| | 801.12 | Crown Transition/Crown Runoff (CR) Table | 7/01 | | | |
| | 801.13 | Table 1 | ., | | | |
| | 801.14 | Table 2 | | | | |
| | 801.15 | Design Superelevation Rates Urban Conditions | | | | |
| TC-5 | 801.16 | Design Superelevation Rates Rural Conditions | | | | |
| | 801.17 | Methodologies for Calculating TC-5 Values for Urban Low-Speed Streets | | | | |
| | 801.18 | Methodologies for Calculating TC-5 Values | | | | |
| | 801.19 | Calculated TC-5 Examples | | | | |
| | 801.20 | Summary of Standard TC-5ULS (Urban Low Speed) Design Factors | | | | |
| | 801.21 | Design Factors for a Design Speed of 20 mph (Urban) | | | | |
| | 801.22 | Design Factors for a Design Speed of 25 mph (Urban) | | | | |
| | 801.23 | Design Factors for a Design Speed of 30 mph (Urban) | | | | |
| | 801.24 | Design Factors for a Design Speed of 35 mph (Urban) | | | | |
| | 801.25 | Design Factors for a Design Speed of 40 mph (Urban) | | | | |
| | 801.26 | Design Factors for a Design Speed of 45 mph (Urban) | | | | |
| | 801.27 | Design Factors for a Design Speed of 50 mph (Urban) | | | | |
| | 801.28 | Design Factors for a Design Speed of 55 mph (Urban) | | | | |
| | 801.29 | Design Factors for a Design Speed of 60 mph (Urban) | | | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|--|-----------|---------|---------|---------|
| l | 801.30 | Design Factors for a Design Speed of 20 mph (Rural) | | | | |
| | 801.31 | Design Factors for a Design Speed of 25 mph (Rural) | | | | |
| | 801.32 | Design Factors for a Design Speed of 30 mph (Rural) | | | | |
| | 801.33 | Design Factors for a Design Speed of 35 mph (Rural) | | | | |
| | 801.34 | Design Factors for a Design Speed of 40 mph (Rural) | | | | |
| TC-5 | 801.35 | Design Factors for a Design Speed of 45 mph (Rural) | | | | |
| | 801.36 | Design Factors for a Design Speed of 50 mph (Rural) | | | | |
| | 801.37 | Design Factors for a Design Speed of 55 mph (Rural) | | | | |
| | 801.38 | Design Factors for a Design Speed of 60 mph (Rural) | | | | |
| | 801.39 | Design Factors for a Design Speed of 65 mph (Rural) | | | | |
| | 801.40 | Design Factors for a Design Speed of 70 mph (Rural) | | | | |
| | 802.01 | Transition Curves for Rural and Urban Highways and Street Conditions | New 10/02 | | | |
| | 802.02 | Explanation of Tables and Instructions for use - Urban Condition | New 10/02 | | | |
| | 802.03 | Explanation of Tables and Instructions for use - Rural Condition | New 10/02 | | | |
| | 802.04 | Explanation of Tables and Instructions for use - General Condition | New 10/02 | | | |
| | 802.05 | Details for Transitioned Baseline Rural Condition With Pavement Widening | New 10/02 | | | |
| | 802.06 | Details for Non-Transitioned Baseline Urban Conditions and Rural Condition Without Pavement Widening | New 10/02 | | | |
| | 802.07 | Details of Superelevation About Baseline | New 10/02 | | | |
| TC-5.01 | 802.08 | Details of Superelevation About Baseline | New 10/02 | | | |
| | 802.09 | Example for Four Lane Roadways | New 10/02 | | | |
| | 802.10 | Cross Section - Four Lane Roadway | New 10/02 | | | |
| | 802.11 | Method of Applying TC-5.01 on Compound Curves Rural Condition With Pavement Widening | New 10/02 | | | |
| | 802.12 | Method of Applying TC-5.01 on Reverse Curves Rural Condition With Pavement Widening | New 10/02 | | | |
| | 802.13 | Method of Applying TC-5.01 on Compound Curves Urban & Rural Condition Without Pavement Widening | New 10/02 | 3/03 | | |
| | 802.14 | Method of Applying TC-5.01 on Reverse Curves Urban & Rural Condition Without Pavement Widening | New 10/02 | 3/03 | | |

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|--------|---|-----------|---------|---------|---------|
| | 802.15 | Blank Sheet | | | | |
| | 802.16 | Crown Transition/Crown Runoff (CR) Table | New 10/02 | | | |
| | 802.17 | Table 1 | New 10/02 | | | |
| | 802.18 | Table 2 | New 10/02 | | | |
| | 802.19 | Design Superelevation Rates Urban Conditions | New 10/02 | | | |
| | 802.20 | Design Superelevation Rates Rural Conditions | New 10/02 | | | |
| | 802.21 | Methodologies for Calculating TC-5.01 Values for Urban Low-Speed Streets | | | | |
| | 802.22 | Methodologies for Calculating TC-5.01 Values | | 3/03 | | |
| | 802.23 | Calculated TC-5.01 Examples | New 10/02 | | | |
| | 802.24 | Summary of Standard TC-5.01 ULS (Urban Low Speed) Design Factors | New 10/02 | | | |
| | 802.25 | Design Factors for a Design Speed of 20 mph (Urban) | New 10/02 | | | |
| | 802.26 | Design Factors for a Design Speed of 25 mph (Urban) | New 10/02 | | | |
| | 802.27 | Design Factors for a Design Speed of 30 mph (Urban) | New 10/02 | | | |
| | 802.28 | Design Factors for a Design Speed of 35 mph (Urban) | New 10/02 | | | |
| | 802.29 | Design Factors for a Design Speed of 40 mph (Urban) | New 10/02 | | | |
| TC-5.01 | 802.30 | Design Factors for a Design Speed of 45 mph (Urban) | New 10/02 | | | |
| | 802.31 | Design Factors for a Design Speed of 50 mph (Urban) | New 10/02 | | | |
| | 802.32 | Design Factors for a Design Speed of 55 mph (Urban) | New 10/02 | | | |
| | 802.33 | Design Factors for a Design Speed of 60 mph (Urban) | New 10/02 | | | |
| | 802.34 | Design Factors for a Design Speed of 20 mph (Rural) | | 3/03 | 1/04 | |
| | 802.35 | Design Factors for a Design Speed of 25 mph (Rural) | New 10/02 | 3/03 | 1/04 | |
| | 802.36 | Design Factors for a Design Speed of 30 mph (Rural) | New 10/02 | 3/03 | | |
| | 802.37 | Design Factors for a Design Speed of 35 mph (Rural) | New 10/02 | 3/03 | 1/04 | |
| | 802.38 | Design Factors for a Design Speed of 40 mph (Rural) | New 10/02 | 3/03 | | |
| | 802.39 | Design Factors for a Design Speed of 45 mph (Rural) | New 10/02 | 3/03 | | |
| | 802.40 | Design Factors for a Design Speed of 50 mph (Rural) | New 10/02 | 3/03 | | |
| | 802.41 | Design Factors for a Design Speed of 55 mph (Rural) | New 10/02 | 3/03 | | |
| | 802.42 | Design Factors for a Design Speed of 60 mph (Rural) | New 10/02 | 3/03 | | |

| Standard | Page | Title | Revised | | Revised | Revised |
|----------|--------|---|-----------|------|---------|---------|
| | | Design Factors for a Design Speed of 65 mph (Rural) | | | | |
| | 802.44 | Design Factors for a Design Speed of 70 mph (Rural) | New 10/02 | 3/03 | | |

Appendix

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|----------|------|---|---------|---------|---------|---------|
| | Δ_1 | Conversion Table - Inches and Fractions of an Inch in Decimals of a Foot | | | | |
| | A-2 | Standard Reinforcing Bars | | | | |
| | A-3 | Parabolic Vertical Curve Computations | | | | |
| | A-4 | Metric Conversion Factors | | | | |