SIZE OF CENTR POST (FT)	OID MAXIMUM AF			DESIGN TABLE FOR WOOD POST				
	SINGLE-POST	TWO-POST	SIGNS) (FT ²) THREE-POST	COMMENTS				
8	7	13	20					
9	6	12	18					
4" X 4" 10	5	11	16	SEE NOTE 1				
11	5	10	15					
12	4	9	13					
8	18	37	55					
4" X 6" 9	16	33	49					
(SEE 10	15	29	44					
NOTE 2)	13	27	40					
12	12	25	37					
8	15	31	46					
9	14	27	41					
5" X 5" 10	12	24	37					
11	11	22	33					
12	10	20	31					
8	29	58	87					
9	26	51	77					
6" X 6"	23	46	69					
11	21	42	63					
12	19	39	58					
13	18	36	53					
8	52	103	155					
9	46	92	138					
6" X 8"	41	83	124					
(SEE 11	38	75	113					
NOTE 2) 12	34	69	103					
13	32	64	95					
14	22	44	66					

NOTES:

- 1. FOR A SINGLE 4" X 4" POST THE MAXIMUM TOTAL SIGN CAN BE INCREASED TO 16 SQUARE FEET PROVIDED:
 - A. THE MAXIMUM VERTICAL CLEARANCE BETWEEN THE GROUND LEVEL AND BOTTOM OF THE SIGN DOES NOT EXCEED 7'-6" WHILE MAINTAINING A 7'-0" MINIMUM MOUNTING HEIGHT (h) BETWEEN BOTTOM OF SIGN AND TOP OF ROADWAY SURFACE AT THE EDGE OF TRAVEL LANE.
 - B. CONTRACTOR SUPPLIES DEPARTMENT WITH MATERIALS CERTIFICATION FOR WOOD POSTS TO ENSURE CONFORMANCE WITH SECTION 236 OF THE SPECIFICATIONS.
- 2. LARGER DIMENSION OF WOOD POST SHALL BE IN DIRECTION OF (PARALLEL TO) TRAFFIC.
- 3. CENTROID SHALL BE DETERMINED IN ACCORDANCE WITH STANDARD PCS-1.

****VDOT ROAD AND BRIDGE STANDARDS SHEET 3 OF 6 REVISION DATE 02/16 1320.12

A COPY OF THE ORIGINAL SEALED AND SIGNED DRAWING IS ON FILE IN THE CENTRAL OFFICE.

TEMPORARY SIGNS

(FOR CONSTRUCTION, MAINTENANCE, PERMIT AND UTILITY ACTIVITIES) WOOD POST SIGN STRUCTURES

VIRGINIA DEPARTMENT OF TRANSPORTATION

SPECIFICATION REFERENCE

> 512 700