## Appendix 7D-1 Values of Roughness Coefficient n (Uniform Flow)

Type of Channel and Description	Minimum	Normal	Maximum
LINED CHANNELS (Selected linings)			
a. Concrete			
1. Trowel finish	0.011	0.013	0.015
2. Float finish	0.013	0.015	0.016
<ol><li>Gunite, good section</li></ol>	0.016	0.019	0.023
b. Asphalt			
1. Smooth	0.013	0.013	-
2. Rough	0.016	0.016	-
c. Riprap (st'd VDOT sizes)	0.000	0.000	
1. Class 1A	0.033	0.038	-
2. Class 1	0.035	0.040	-
3. Class 2	0.037	0.042	
4. Class 3	0.039	0.045	
5. Type I 6. Type II	0.041 0.044	0.047 0.050	
б. Туре п	0.044	0.050	-
EXCAVATED OR DREDGED			
a. Earth, straight and uniform			
Clean, recently completed	0.016	0.018	0.020
2. Clean, after weathering	0.018	0.022	0.025
3. Gravel, uniform section, clean	0.022	0.025	0.030
4. With short grass, few weeds	0.022	0.027	0.033
b. Earth, winding and sluggish	0.022	0.02.	0.000
1. No vegetation	0.023	0.025	0.030
2. Grass, some weeds	0.025	0.030	0.033
3. Dense weeds or aquatic plants in deep channels		0.035	0.040
4. Earth bottom and rubble sides	0.025	0.030	0.035
<ol><li>Stony bottom and weedy sides</li></ol>	0.025	0.035	0.045
6. Cobble bottom and clean sides	0.030	0.040	0.050
c. Dragline excavated or dredged			
1. No vegetation	0.025	0.028	0.033
<ol><li>Light brush on banks</li></ol>	0.035	0.050	0.060
d. Rock cuts			
<ol> <li>Smooth and uniform</li> </ol>	0.025	0.035	0.040
<ol><li>Jagged and irregular</li></ol>	0.035	0.040	0.050
e. Channels not maintained, weeds and brush uncut			
<ol> <li>Dense weeds, high as flow depth</li> </ol>	0.050	0.080	0.120
<ol><li>Clean bottom, brush on sides</li></ol>	0.040	0.050	0.080
3. Same, highest stage of flow	0.045	0.070	0.110
4. Dense brush, high stage	0.080	0.100	0.140
NATUDAL CTDEAMC			
NATURAL STREAMS  1. Minor streams (top width at flood stage <100 ft)			
a. Streams on Plain			
1. Clean, straight, full stage,			
no rifts or deep pools	0.025	0.030	0.033
2. Same as above, but more stones/weeds	0.025	0.030	0.033
3. Clean, winding, some pools/shoals	0.030	0.040	0.045
4. Same as above, but some weeds/stones	0.035	0.045	0.050
5. Same as above, lower stages,	0.000	0.0-10	0.000
more ineffective slopes and sections	0.040	0.048	0.055
6. Same as 4, but more stones	0.045	0.050	0.060
7. Sluggish reaches, weedy, deep pools	0.050	0.030	0.080
	0.000	2.0.0	2.000

\* Rev 7/09

Appendix 7D-1 Values of Roughness Coefficient n (Uniform Flow)

Type of Channel and Description		Normal	Maximum
8. Very weedy reaches, deep pools, or floodways with heavy stand of timber and underbrush b. Mountain streams, no vegetation in channel, banks usually steep, trees and brush along	0.075	0.100	0.150
banks submerged at high stages	0.030	0.040	0.050
	0.040	0.050	0.070
Floodplains     a. Pasture, no brush			
	0.025	0.030	0.035
3 3	0.030	0.035	0.050
b. Cultivated area			
	0.020	0.030	0.040
	0.025	0.035	0.045
	0.030	0.040	0.050
c. Brush			
	0.035	0.050	0.070
3	0.035	0.050	0.060
3	0.040	0.060	0.080
	0.045	0.070	0.110
	0.070	0.100	0.160
d. Trees			
Dense Willows, summer, straight     Cleared land with tree stumps, no	0.110	0.150	0.200
sprouts 3. Same as above, but with heavy	0.030	0.040	0.050
growth of sprouts  4. Heavy stand of timber, a few down trees, little undergrowth, flood stage	0.050	0.060	0.080
	0.080	0.100	0.120
	0.100	0.120	0.160
3. Major Streams (top width at hood stage > 100 ft)			
The n-value is less than that for minor streams of similar description, because banks offer less effective resistance.			
	0.025 0.035	-	0.060 0.100

Source: Chow, V.T., FHWA's HDS-6 publication\*

\_

<sup>\*</sup> For bare earth linings when the soil classifications in accordance with either AASHTO or USCS designations are known, use the Manning's "n" values recommended in the appropriate table from Appendix 7D-2

<sup>\*</sup> Rev 7/09