

APPENDIX B(2)

MULTIMODAL DESIGN STANDARDS FOR MIXED-USE URBAN CENTERS

SECTION B(2) - 1 – INTRODUCTION

| | |
|--|--------|
| Introduction..... | B(2)-1 |
| Fundamental Concepts and Definitions | B(2)-5 |

SECTION B(2) – 2 – ROADWAY GEOMETRIC DESIGN CRITERIA

| | |
|-------------------------------------|---------|
| Geometric Design Standards..... | B(2)-9 |
| Intersection Spacing Standards..... | B(2)-9 |
| Stopping Sight Distance | B(2)-11 |
| Intersection Sight Distance | B(2)-12 |
| Sight Distance Triangle | B(2)-12 |

SECTION B(2) - 3 - ELEMENTS OF TYPICAL SECTION

| | |
|--|---------|
| Bicycle and Pedestrian Facilities | B(2)-13 |
| Parallel On-Street Parking Lane Widths | B(2)-13 |
| Curb Extensions (Bulb-Outs) | B(2)-13 |
| Curb Radii – Actual and Effective | B(2)-14 |
| Turn Lane Tapers | B(2)-15 |
| Roadway Drainage | B(2)-15 |
| Right of Way | B(2)-15 |

SECTION B(2) – 4 - OTHER DESIGN CONSIDERATIONS

| | |
|--|---------|
| Clear Zone..... | B(2)-16 |
| Traffic Calming | B(2)-16 |
| Roundabouts | B(2)-16 |
| Maintenance Items | B(2)-16 |
| Utility Placement..... | B(2)-16 |
| Roadway Lighting | B(2)-16 |
| Sidewalk/Crosswalk Pavers..... | B(2)-17 |
| Streetscape and Landscape Considerations | B(2)-17 |
| Activity Center Amenities Summary | B(2)-17 |