

GEOMETRIC DESIGN STANDARDS FOR RURAL PRINCIPAL ARTERIAL SYSTEM (GS-1)

	TERRAIN	DESIGN SPEED (MPH)	MINIMUM RADIUS	(6) MINIMUM STOPPING SIGHT DISTANCE	MIN. WIDTH OF LANE	(1) MINIMUM WIDTH OF TOTAL SHOULDERS (GRADED & PAVED) CUT & FILL		(2) MINIMUM PAVED SHOULDER WIDTH		(3) MINIMUM WIDTH OF DITCH FRONT SLOPE	(4) SLOPE	NEW AND RECONSTRUCTED MINIMUM BRIDGE WIDTHS AND VERTICAL CLEARANCES See Footnote (5)
						With GR	Without GR	LT.	RT.			
FREEWAYS	LEVEL	75	2215'	820'	12'	16'	12'	4'	10'	12' @ 6:1	CS-4B	
		70	1821'	730'								
	ROLLING	60	1204'	570'							CS-4E	
MOUNTAINOUS	50	760'	425'									
OTHER PRINCIPAL ARTERIALS	LEVEL	70	1821'	730'	12'	14'	10'	4'	8'	10' @ 6:1	CS-4/	
		60	1204'	570'							CS-4B	
	ROLLING	60	1204'	570'						CS-4/		
		50	760'	425'							CS-4E	
	MOUNTAINOUS	50	760'	425'						6' @ 4:1	CS-3/	
		45	589'	360'								CS-3B
		40	446'	305'								

GENERAL NOTES

Freeways - A design speed of 75 mph should be used for Rural Freeways. Where terrain is mountainous, a design speed of 60 mph or 50 mph which is consistent with driver expectancy, may be used.

Other Principal Arterials - A design speed of 40 to 70 mph should be used depending on terrain, driver expectancy and whether the design is constructed on new location or reconstruction of an existing facility. An important safety consideration in the selection of one of the lower design speeds in each range is to have a properly posted speed limit.

Incorporated towns or other built-up areas, Urban Standard GS-5 may be used for design. "Built-up" is where there is sufficient development along the roadway that justifies a need to channelize traffic into and out of properties utilizing curb and gutter.

Standard TC-5.11R superelevation based on 8% maximum is to be used for all Rural Principal Arterials.

Clear Zone and Recoverable Area information can be found in Appendix A, Section A-2 of the Road Design Manual.

If medians are included, see Section 2E-3 of Chapter 2E of the Road Design Manual.

For additional information on roadway widths and maximum grades relative to terrain and design speed, see AASHTO Green Book, Chapter 7, Section 7.2.2, page 7-4, Tables 7-2 and Section 7.2.3, page 7-5, Table 7-3; for Freeways, see Chapter 8, Section 8.2.7, page 8-4, Table 8-1.

FOOTNOTES

- (1) Total shoulder widths include the paved portion and are applicable to the left and right shoulder.
On Freeways, if truck traffic exceeds 250 DDHV, a wider total shoulder should be considered (14' without guardrail and 18' with guardrail).
- (2) When the mainline is 6 or more lanes, the left paved shoulder width shall be the same as the right paved shoulder. On Freeways, if truck traffic exceeds 250 DDHV, a wider right paved shoulder should be considered (12').
- (3) A hydraulic analysis is necessary to determine actual depth requirement.
- (4) Additional or modified slope criteria to apply where shown on typical sections.
- (5) See Manual of the Structure and Bridge Division – Volume V – Part 2 Design Aids – Chapter 6 Geometrics.
- (6) For additional information on sight distance requirements on grades of 3 percent or greater, see Section 3.2.2, page 3-5, Tables 3-2 of the AASHTO Green Book.

FIGURE A - 1 - 1*