

TABLE A-5-7 MINIMUM RADII FOR PAVED SHARED USE PATHS BASED ON 15° LEAN ANGLE	A-98
TABLE A-5-8 MAXIMUM GRADE LENGTHS.....	A-98
TABLE A-5-9 MINIMUM STOPPING SIGHT DISTANCE (FT.) DESCENDING GRADE	A-99
TABLE A-5-10 MINIMUM STOPPING SIGHT DISTANCE (FT.) ASCENDING GRADE	A-99
TABLE A-5-11 MINIMUM LENGTH OF CREST VERTICAL CURVE (L) BASED ON STOPPING SIGHT DISTANCE.....	A-100
FIGURE A-5-8 MINIMUM CLEARANCE FOR LINE OF SIGHT	A-101
TABLE A-5-12 MINIMUM LATERAL CLEARANCE FOR HORIZONTAL CURVES	A-101
FIGURE A-5-9 SHARED USE PATH TRANSITION FROM ROADWAY ONTO BRIDGE	A-104
FIGURE A-5-10 INTERSTATE BICYCLE ROUTE 1 AND 76	A-105
FIGURE A-5-11 SEPARATION BETWEEN ACTIVE RAIL LINES AND PATHS (RWT).....	A-106
TABLE A-5-13 SEPARATION BETWEEN ACTIVE RAIL LINES AND PATHS (RWT).....	A-107
FIGURE A-5-12 SIDEWALK TRANSITION FROM ROADWAY ONTO BRIDGE	A-120