



# ABUTMENTS, RIPRAP & SHORING



Keith Weakley, PE

Bridge Construction Inspection School


## Abutments










## Abutment Loads & Terminology



## Gravity Abutment







## MSE Abutment




## MSE Abutments (Shop Drawings)



## MSE Abutment



## Traditional Abutment



## Traditional Abutment




## Water Damage at Joints



# Integral Bridges



# Integral Abutment




## Integral Abutment




## Integral Abutment




## Beam Support



## Dowels





### Semi-Integral

Projection of Beam  
into Integral Backwall



Drip Bead  
Formwork

### Semi-Integral-Forming




Formwork should  
NOT be attached to  
the substructure.

### Semi-Integral




### Deck Extension







**Rub Plates**




**Rub Plates**



## Semi-Integral



SEMI-INTEGRAL ABUTMENT – WITH DECK CLOSURE DETAIL




SEMI-INTEGRAL ABUTMENT - WITHOUT DECK CLOSURE DETAIL

## Backfilling Integrals




## Structural Backfill



**SECTION THROUGH ABUTMENT - CUT SECTION**


Abutment drainage not shown  
Not to scale

## Structural Backfill



**SECTION THROUGH ABUTMENT - FILL SECTION**

## Elastic Inclusion (EPS)




**SECTION**  
(Showing Semi-Integral)

## Elastic Inclusion (EPS)



## Virginia Abutment



## Virginia Abutment



## Virginia Abutment



## Virginia Abutment



## Weepholes




## Weep Holes



Weep holes are necessary to reduce water pressure behind the abutment. It is critical that they are installed correctly, since they are part of the design.

## Weep Holes




“Lowest Point Feasible for Free Drainage” means as low as you can get it, but still be above the ground, once all of the final grading has been completed. The weep hole will be the top of the water table behind the abutment, so it needs to be as low as possible to minimize the water pressure.

## Weep Holes



“Lowest Point Feasible for Free Drainage” means as low as you can get it, but still be above the ground, once all of the final grading has been completed. The weep hole will be the top of the water table behind the abutment, so it needs to be as low as possible to minimize the water pressure.

## Weep Hole Alternatives



You may encounter abutments that have no weep hole, but instead a piped drainage system. Just ensure this is installed per plan and “daylighted” so that it drains properly.

## Weep Hole Alternatives



You may encounter abutments that have no weep hole, but instead a piped drainage system. Just ensure this is installed per plan and “daylighted” so that it drains properly.

## Wall Drain




Geocomposite Wall Drains (Ameridrain, Miradrain, etc).  
See Sec. 401.03 (2016 Specs).

- Overlap
- Filter Fabric
- Installation

## Tooth Expansion Joints (Finger Joints)



## Tooth Expansion Joints (Finger Joints)



PART SECTION AT CONCRETE BEAM

## Tooth Expansion Joints



## Tooth Expansion Joints



## Tooth Expansion Joints-Things to remember

- Alignment is extremely important!
- Realignment will likely be necessary after the deck pour(s). Both Vertical and Horizontal.
- The Construction Joint at the Finger Joint is there for a reason!


## Approach Slabs




## Traditional Approach Slabs




### Traditional Approach Slabs



### Buried Approach Slabs




### Buried Slabs



### Buried Approach Slabs



## Shoring



## Pier Excavation



## Sheet Piling



## Sheeting & Attachments




## Soldier Piles



## Soldier Piles



**Soldier Piles**




**Tie Backs**



Welding waler - 9/23/02

## Strut & Waler



## Shoring



### Things to keep in Mind

- When driving sheeting/piles, be sure that the depth reached meets or exceeds that specified by the approved shoring plans.
- Closely inspect all connections, especially those to, or near the abutments, as this is usually the deepest part of the excavation.
- Be sure to compare the approved plans to what is actually built in the field. If there are any differences, let someone know!

### Things to keep in Mind

- Most important, lives may be at stake. The shoring may be holding up the roadway, but at a minimum is holding the excavation open for the workers & Inspectors.
- Closely monitor the shoring for movement. If you are unsure whether there is a danger-call your Construction Manager, or the Bridge office.

## Shoring Payment

### TEMPORARY SHORING NOTES:

Temporary shoring utilized by the Contractor to support the existing and proposed structures and roadway while open to the traveling public shall be designed by a registered professional engineer holding a valid license to practice engineering in the Commonwealth of Virginia. Working drawings and design calculations of the shoring shall be submitted to the Engineer for review 30 days prior to installation of the shoring in accordance with Section 105.10. The drawings shall include plan and profile views, details of sheet piling, walers, rakers, connections, welds, fasteners, all structural members, soldier piles, tiebacks or other means of support as determined by the Contractor and his Engineer. The Contractor shall determine the methods and means of support required for the loads imposed by the roadway, traffic, the structure and any loads imposed by construction equipment during the construction of the project.

Approximate limits of temporary shoring shown on the plans are for informational purposes only. The Contractor shall be responsible for determining the actual limits and quantities of temporary shoring. The limits of temporary shoring shall be defined as that length necessary for structure excavation or minor structure excavation, and for maintaining minimum temporary slopes in accordance with OSHA requirements around the limits of structure excavation or minor structure excavation for each stage of construction. The cost of the design, installation, and removal of the temporary shoring, when no longer required, shall be included in the bid price for the temporary shoring for both stages. This price shall be full compensation for all labor, tools, materials, equipment, and incidentals required for the satisfactory completion of the work. This price shall include all temporary shoring required for construction of the structure whether or not shown on the plans. Temporary shoring shall be paid for on a lump sum basis and shall include both construction phases.

- In response to claims, and in an effort to reduce them, the Temporary Shoring bid item has been changed from Square Yard to Lump Sum. Check the plans for your specific job for the verbiage, but you should find that the Lump Sum bid item includes anything required to retain the excavation.

## Crib Walls



### Wire Wall



### Slope Protection & Riprap



## Riprap


### VDOT Specifications

- Class III Rip-Rap - **500-1500lbs** At least 50% weigh more than 900lbs and approximately 10% may weigh less than 500lbs
- Class II Rip-Rap - **150-500lbs** At least 50% weigh more than 300lbs and approximately 10% may weigh less than 150lbs
- Class I Rip-Rap - **50-150lbs** At least 60% weigh more than 100lbs and approximately 10% may weigh less than 50lbs
- Class I-A Rip-Rap - **25-75lbs** approximately 10% may weigh less than 25lbs and 10% may weigh 75-100lbs
- Gabion - **4-30lbs** 5% may weigh less than 4lbs or more than 30lbs At least 50% weigh more than 10lbs



## Riprap

### Reference Size's




The measurements listed above are the circumference of each ball




## Riprap

### Class III Rip-Rap




## Riprap

### Class II Rip-Rap




## Riprap

### Class I Rip-Rap



## Riprap



## Riprap




Filter Fabric

Aggregate Material

These are important to prevent fines from washing through and causing the riprap to fail. They are part of the scour protection system, along with the riprap.


## Grouted Riprap



## Grouted Riprap-WRONG!



## Concrete Slope Protection



## Concrete Slope Protection



## Things to keep in Mind

- If the plan details show bedding material and filter cloth, then make sure the contractor installs these items.
- The correct installation of riprap/slope protection will almost always require excavation. Unless specified otherwise, the contractor does not get paid for this excavation.

### Things to keep in Mind

- When installing grouted riprap, pay particular attention to the plan details. "Grouted" does not mean "flooded". The grout should barely be visible from the surface.
- When installing riprap in the stream, refer to the environmental permit sketch in the contract. This will direct what operations are allowed. Any deviation must be cleared with the Environmental



### Questions