

**RURAL EXAMPLE**

20 FT PAVEMENT WIDTH  
(DESIGN SOFTWARE - 1 LANE AT 10 FT)

$V_D = 50$  MPH                       $R = 1000$  FT  
 $W_n = 10$  FT                       $rg = 0.50$   
 $E = 7.6$  (7.6% PER 802.40)

$U = u + R - \sqrt{R^2 - L^2}$   
 $U = 8.0 + 1000 - \sqrt{(1000)^2 - (20)^2}$   
 $U = 8.20002$

$F_A = \sqrt{R^2 + A(2L + A)} - R$   
 $F_A = \sqrt{(1000)^2 + 4[2(20) + 4]} - 1000$   
 $F_A = .087996$

$Z = (V_D / \sqrt{R})$   
 $Z = (50 / \sqrt{1000})$   
 $Z = 1.58$

$W_C = N(U + C) + F_A + Z$   
 $W_C = 2(8.20002 + 2) + 0.087996 + 1.58$   
 $W_C = 22.0680$

$w = W_C - 2W_n = 22.0680 - 2(10) = 2.1$

( $R < 2865$  &  $w > 2$  THEREFORE WIDENING IS REQUIRED)  
 $LS = [E n_1 (W_n + w/2) / rg] b_w$   
 $LS = [7.6(1)(10 + 2.1/2) / 0.50] 1$   
 $LS = 7.6 (11.05) / 0.50$   
 $LS = 167.96$

**RURAL EXAMPLE**

72 FT PAVEMENT WIDTH  
(DESIGN SOFTWARE - 3 LANES AT 12 FT)

$V_D = 40$  MPH                       $R = 500$  FT  
 $W_n = 12$  FT                       $rg = 0.58$   
 $E = 8.0$  (8% PER PAGE 802.38)

$U = u + R - \sqrt{R^2 - L^2}$   
 $U = 8.0 + 500 - \sqrt{(500)^2 - (20)^2}$   
 $U = 8.4002$

$F_A = \sqrt{R^2 + A(2L + A)} - R$   
 $F_A = \sqrt{(500)^2 + 4[2(20) + 4]} - 500$   
 $F_A = .1760$

$Z = (V_D / \sqrt{R})$   
 $Z = (40 / \sqrt{500})$   
 $Z = 1.7885$

$W_C = 2(U + C) + F_A + Z$   
 $W_C = 2(8.4002 + 3.0) + .1760 + 1.7885$   
 $W_C = 24.7651$

$w = W_C - 2W_n = 24.7651 - 2(12) = 0.7651(0.8)$

FOR 72' PAVEMENT WIDTH  
 $w = 3(0.8) = 2.4$

( $R < 881$  &  $w > 2$  THEREFORE WIDENING IS REQUIRED)  
 $LS = [E n_1 (W_n + w/3) / rg] b_w$   
 $LS = [8 (3) (12 + 2.4/3) / 0.58] 0.6667$   
 $LS = (307.2 / 0.58) 0.6667$   
 $LS = 353.1211$   
 OR  
 $LS = MCE(W_n + w/N) / rg$   
 $LS = 2 [8(12 + 4.5/3) / 0.58]$   
 $LS = 2 (102.4 / 0.58)$   
 $LS = 353.1034$

**URBAN EXAMPLES**

24 FT PAVEMENT WIDTH  
(DESIGN SOFTWARE - 1 LANE AT 12 FT)

$V_D = 40$  MPH                       $R = 600$  FT  
 $W_n = 12$  FT                       $rg = 0.58$   
 $E = 4.0$  (4% PER PAGE 802.29)

$LS = (W_n n_1 E / rg) b_w$   
 $LS = [12(1)(4) / 0.58] 1.00$   
 $LS = (48 / 0.58)$   
 $LS = 82.7586$

66 FT PAVEMENT WIDTH  
(DESIGN SOFTWARE - 3 LANES AT 11 FT)

$V_D = 40$  MPH                       $R = 600$  FT  
 $W_n = 11$  FT                       $rg = 0.58$   
 $E = 4.0$  (4% PER PAGE 801.29)

$LS = b_w (W_n n_1 E / rg)$   
 $LS = 0.6667 [11(3)(4) / 0.58]$   
 $LS = 0.6667 (132 / 0.58)$   
 $LS = 151.7317$

OR

$LS = M (E W_n / rg)$   
 $LS = 2 [4(11) / 0.58]$   
 $LS = 2 (44 / 0.58)$   
 $LS = 151.7241$

**CALCULATED TC-5.01 EXAMPLES**