

PIPE GRATE

TYPE I - 3½" O.D.
TYPE II - 4" O.D.
TYPE III - 4½" O.D.

LENGTH OF GRATE TO BE DETERMINED
BY L₂ X NUMBER OF PIPES REQUIRED

4 : 1 SLOPE

PIPE SIZE	H	L	W	T	PIPE O.D.	NO. PIPES REQUIRED	L ₂	L ₃	L ₄	L ₅
					3½"	1	8'-6¾"			
12"	1'-10"	7'-4"	2'-0"	8"	3½"	1	8'-6¾"			
15" or 18"	2'-4½"	9'-6"	2'-0"	8"	3½"	1	10'-9½"			
21" or 24"	2'-11"	11'-8"	3'-0"	8"	4"	2	13'-0¼"			
27" or 30"	3'-5½"	13'-10"	3'-0"	8"	4"	2	15'-3"			
33" or 36"	4'-0"	16'-0"	4'-0"	8"	4½"	3	17'-6"			
42"	4'-6½"	18'-2"	4'-0"	12"	4½"	3	19'-8¾"			
48"	5'-1"	20'-4"	5'-0"	12"	4½"	3	22'-2½"	10'-5¼"	11'-10½"	10'-4¼"
54"	5'-7½"	22'-6"	6'-0"	12"	4½"	4	24'-5½"	12'-8½"	11'-10½"	12'-7½"
60"	6'-2"	24'-8"	6'-0"	12"	4½"	4	26'-8½"	14'-11"	11'-10½"	14'-10"

NO CENTER SUPPORT REQUIRED

DIMENSIONS FOR BEVEL
ON HEADWALL

PIPE I.D.	a	b
12"	0'-1¼"	0'-1"
15" or 18"	0'-2"	0'-1½"
21" or 24"	0'-2½"	0'-2"
27" or 30"	0'-3¼"	0'-2½"
33" or 36"	0'-3¾"	0'-3"
42"	0'-4½"	0'-3½"
48"	0'-5"	0'-4"
54"	0'-5¾"	0'-4½"
60"	0'-6¼"	0'-5"

6 : 1 SLOPE

PIPE SIZE	H	L	W	T	PIPE O.D.	NO. PIPES REQUIRED	L ₂	L ₃	L ₄	L ₅
					3½"	1	12'-1¾"			
12"	1'-10"	11'-0"	2'-0"	8"	3½"	1	12'-1¾"			
15" or 18"	2'-4½"	14'-3"	2'-0"	8"	4"	1	15'-5¼"			
21" or 24"	2'-11"	17'-6"	3'-0"	8"	4½"	2	18'-9"			
27" or 30"	3'-5½"	20'-9"	3'-0"	8"	4½"	2	22'-0"	4'-8½"	17'-4½"	4'-7½"
33" or 36"	4'-0"	24'-0"	4'-0"	8"	4½"	3	25'-3¾"	7'-11½"	17'-4½"	7'-11"
42"	4'-6"	27'-3"	4'-0"	12"	4½"	3	28'-11"	11'-7¼"	17'-4½"	11'-6½"
48"	5'-1"	30'-6"	5'-0"	12"	4½"	3	32'-2"	14'-10¾"	17'-4½"	14'-10½"
54"	5'-7½"	33'-9"	6'-0"	12"	4½"	4	35'-6"	18'-2½"	17'-4½"	18'-1½"
60"	6'-2"	37'-0"	6'-0"	12"	4½"	4	38'-9½"	19'-5½"	19'-4¾"	19'-4¾"

NO CENTER SUPPORT REQUIRED

3 : 1 SLOPE

PIPE SIZE	H	L	W	T	PIPE GRATE			NO. CENTER SUPPORT REQUIRED
					PIPE O.D.	NO. PIPES REQUIRED	L ₂	
12"	1'-10"	5'-6"	2'-0"	8"	3½"	1	6'-9½"	
15" or 18"	2'-4½"	7'-1½"	2'-0"	8"	3½"	1	8'-6¾"	
21" or 24"	2'-11"	8'-9"	3'-0"	8"	3½"	2	10'-2¾"	
27" or 30"	3'-5½"	10'-4½"	3'-0"	8"	3½"	2	11'-11¾"	
33" or 36"	4'-0"	12'-0"	4'-0"	8"	4"	3	13'-7¾"	
42"	4'-6½"	13'-7½"	4'-0"	12"	4"	3	15'-4¼"	
48"	5'-1"	15'-3"	5'-0"	12"	4½"	3	17'-0½"	
54"	5'-7½"	16'-10½"	6'-0"	12"	4½"	4	18'-9½"	
60"	6'-2"	18'-6"	6'-0"	12"	4½"	4	20'-6"	

APPROXIMATE QUANTITIES

PIPE SIZE	3 : 1			PIPE SIZE	4 : 1			PIPE SIZE	6 : 1		
	CONCRETE CUBIC YARDS	lbs. REINF.	PIPE SIZE		CONCRETE CUBIC YARDS	lbs. REINF.	PIPE SIZE		CONCRETE CUBIC YARDS	lbs. REINF.	
12"	.95	.97	12"	1.17	1.18	308	12"	1.64	1.66	443	
15" or 18"	1.27	1.29	328	15" or 18"	1.59	1.61	425	15" or 18"	2.28	2.31	618
21" or 24"	2.30	2.35	483	21" or 24"	2.44	2.49	628	21" or 24"	3.55	3.59	917
27" or 30"	2.38	2.44	608	27" or 30"	3.01	3.01	788	27" or 30"	4.35	4.41	1157
33" or 36"	3.28	3.38	809	33" or 36"	4.20	4.29	1059	33" or 36"	6.01	6.09	1556
42"	6.27	6.46	1050	42"	8.05	8.22	1368	42"	11.59	11.76	1997
48"	8.07	8.29	1327	48"	10.29	10.50	1647	48"	14.84	15.04	2514
54"	10.02	10.29	1612	54"	12.80	13.06	2105	54"	18.47	18.73	3094
60"	11.18	11.50	1826	60"	14.36	14.68	2391	60"	20.82	21.14	3517



PIPE ENDWALL WITH LOAD-CARRYING GRATE

12" - 60" CIRCULAR PIPES

VIRGINIA DEPARTMENT OF TRANSPORTATION