

URBAN LOW SPEED DESIGN TABLE

DV/NC	MAX. f	C	LS
45	0.161	2.75	140
40	0.178	3.00	120
35	0.197	3.25	120
30	0.221	3.50	100
25	0.252	3.75	90
20	0.300	4.00	90

LEGEND

- C- RATE OF CHANGE OF SIDE FRICTION (f) IN FT./SEC.³
- e- SUPERELEVATION RATE IN PERCENT.
- f- FRICTION FACTOR.
- LS- LENGTH OF SUPERELEVATION TRANSITION.
- R- RADIUS OF CURVE.
- DV- DESIGN VELOCITY UTILIZING SUPERELEVATION.
- NC- MAXIMUM VELOCITY WITH NO SUPERELEVATION (NORMAL CROWN).

FRICTION FACTORS (f) FOR ODD VELOCITIES NOT LISTED SHOULD BE DERIVED BY INTERPOLATION.

FOR LS LENGTHS FOR INTERMEDIATE VELOCITIES NOT LISTED IN TABLE USE THE LS FOR NEXT LOWER VELOCITY IN TABLE.

GENERAL DESIGN CONSIDERATIONS

1. WHEN "URBAN LOW SPEED" DESIGNS UTILIZE SUPERELEVATION, THEY WILL BE SUPERELEVATED BY AN AMOUNT EQUAL TO THE NORMAL CROWN (TYPICALLY 2.1%) AND THE APPROXIMATE MAXIMUM SAFE SPEED (DV) AFFORDED THEREBY.
2. WHEN "URBAN LOW SPEED DESIGN" WITH NO SUPERELEVATION, THE APPROXIMATE MAXIMUM SAFE SPEED (NC) IS CALCULATED USING A NEGATIVE NORMAL CROWN (TYPICALLY -2.1%).
3. WHEN THE CURVE IS SUPERELEVATED, THE LS IS APPLIED IN THE SAME MANNER AS IN URBAN CONDITIONS WITH THE CROWN RUNOFF (CR) BEING EQUAL TO THE LS VALUE. THE CROWN RUNOFF (CR) IS ALWAYS ACHIEVED OUTSIDE OF THE TRANSITION (LS).
4. PLEASE NOTE THAT THE RADIUS VALUES LISTED ON PAGE 801.20 HAVE BEEN ROUNDED UP TO THE NEAREST TWENTY FIVE FOOT INCREMENT.

EXAMPLES

DV - 21 mph

e - +2.1%

f = $300 - [1/5(0.300 - 0.252)] - 0.2904$ (ROUND TO 0.29)

LS = $47.2 f DV/C - 47.2(0.29)(21)/4 - 71.862$ FT.

- 71.862 < 90 THEREFORE LS=90 FT.

Rmin. = $(21)^2 / 15(0.021 + 0.29) - 94.53376206$ FT.

NC - 37 mph

e - -2.1%

f = $0.197 - [2/5(0.197 - 0.178)] - 0.1894$ (ROUND TO 0.189)

Rmin. = $(37)^2 / 15(-0.021 + 0.189) - 543.2539683$ FT.

METHODOLOGIES FOR CALCULATING TC-5 VALUES FOR URBAN LOW-SPEED STREETS