

| Standard | Page | Title | Revised | Revised | Revised | Revised |
|------------------|--------|---|---------|---------|---------|---------|
| EW-10 PC | 101.25 | Precast Endwalls for Multiple Pipe Arches 13" - 38" Rise | | | | |
| EW-11 | 101.26 | Pipe Endwall with Load-Carrying Grate for 12" - 60" Pipes | | | | |
| | 101.27 | Pipe Endwall with Load-Carrying Grate for 12" - 60" Pipes | | | | |
| | 101.28 | Pipe Endwall with Load-Carrying Grate for 12" - 60" Pipes | | | | |
| EW-11A | 101.29 | Pipe Endwall with Load - Carrying Grate for 12" - 24" Pipes | | | | |
| | 101.30 | Pipe Endwall with Load - Carrying Grate for 12" - 24" Pipes | | | | |
| EW-11A PC | 101.31 | Precast Pipe Endwall with Load-Carrying Pipe Grate for 12" - 24" Pipes | | | | |
| EW-12 | 101.32 | Endwalls for Pipe Underdrain | 7/03 | | | |
| ES-1 | 102.01 | Flared End-Section for Concrete Pipe Culverts (12"-60") | 7/01 | | | |
| ES-1A | 102.02 | Flared End-Section for 23" X 14" to 53" X 34" Elliptical Concrete Pipe Culverts | 7/01 | | | |
| ES-2 | 102.03 | Flared End-Section for 12" - 60" Corrugated Pipe Culverts | 7/01 | | | |
| ES-3 | 102.04 | Flared End-Section for Metal Pipe Arches 13" - 47" Rise | | | | |
| | 103.01 | Precast Unit Assembly Diagram | | | | |
| | 103.02 | Legend & General Notes - Precast | | | | |
| T-DI-1 | 103.03 | Precast Top Unit - DI-1 | | | | |
| T-DI-2 | 103.04 | Precast Top Unit - DI-2 | 3/03 | | | |
| T-DI-3, 4 | 103.05 | Precast Top Unit - DI-3, DI-4 | 3/03 | | | |
| | 103.06 | Precast Top Unit - DI-3, DI-4 | | | | |
| T-DI-5 | 103.07 | Precast Top Unit - DI-5 | | | | |
| T-DI-7 | 103.08 | Precast Top Unit - DI-7 | | | | |
| T-MH-2 | 103.09 | Precast Manhole Top Units | | | | |
| R-1, 2, 3 | 103.10 | Precast Reducer and Riser Units | | | | |
| B-1, 2 | 103.11 | Precast Base Units | | | | |
| B-3 | 103.12 | Precast Base Unit | | | | |
| B-4 | 103.13 | Corrugated Metal Base Unit | | | | |
| DI-1 | 104.01 | Standard Drop Inlet 12"-24" Pipe: Maximum Depth (H) = 10' | | | | |
| DI-1A | 104.02 | Standard Drop Inlet 12"-24" Pipe: Depth (H) 10' to 20' | | | | |
| DI-2A, 2B, 2C | 104.03 | Standard Curb Drop Inlet 12"-24" Pipe: Maximum Depth (H) = 9' | 1/04 | | | |
| | 104.04 | Dimensions & Quantities | | | | |
| DI-2AA, 2BB, 2CC | 104.05 | Standard Curb Drop Inlet 12"-24" Pipe: Depth (H) = 9' to 20' | | | | |
| DI-2D, 2E, 2F | 104.06 | Standard Curb Drop Inlet 30"-48" Pipe: Maximum Depth (H) = 9' | 1/04 | | | |
| | 104.07 | Dimensions & Quantities | | | | |
| DI-2DD, 2EE, 2FF | 104.08 | Standard Curb Drop Inlet 30"-48" Pipe: Depth (H) = 9' to 20' | | | | |