

DESIGN FACTORS FOR A DESIGN SPEED OF 30 MPH (URBAN) USING E= 4% MAX.													
RADIUS (FEET)	E (%)	PAVEMENT WIDTH											
		24 FT		36 FT		48 FT		60 FT		66 FT		72 FT	
		DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)											
		1 @ 12'		1.5 @ 12'		2 @ 12'		3 @ 10'		3 @ 11'		3 @ 12'	
		CR	LS	CR	LS	CR	LS	CR	LS	CR	LS	CR	LS
3000	NC	0	0	0	0	0	0	0	0	0	0	0	0
1940	2.0	37	37	46	46	55	55	61	61	67	67	73	73
1795	2.1	37	39	46	48	55	58	61	64	67	70	73	77
1658	2.2	37	40	46	50	55	60	61	67	67	74	73	80
1525	2.3	37	42	46	53	55	63	61	70	67	77	73	84
1393	2.4	37	44	46	55	55	66	61	73	67	80	73	88
1255	2.5	37	46	46	57	55	69	61	76	67	84	73	91
1134	2.6	37	48	46	60	55	71	61	79	67	87	73	95
1030	2.7	37	50	46	62	55	74	61	82	67	90	73	99
941	2.8	37	51	46	64	55	77	61	85	67	94	73	102
863	2.9	37	53	46	66	55	80	61	88	67	97	73	106
794	3.0	37	55	46	69	55	82	61	91	67	100	73	110
732	3.1	37	57	46	71	55	85	61	94	67	104	73	113
677	3.2	37	59	46	73	55	88	61	97	67	107	73	117
627	3.3	37	60	46	75	55	90	61	100	67	110	73	120
580	3.4	37	62	46	78	55	93	61	104	67	114	73	124
537	3.5	37	64	46	80	55	96	61	107	67	117	73	128
496	3.6	37	66	46	82	55	99	61	110	67	120	73	131
457	3.7	37	68	46	85	55	101	61	113	67	124	73	135
417	3.8	37	70	46	87	55	104	61	116	67	127	73	139
375	3.9	37	71	46	89	55	107	61	119	67	130	73	142
300	4.0	37	73	46	91	55	110	61	122	67	134	73	146

NOTE:

CR AND LS VALUES IN FEET.

FOR PAVEMENT WIDTHS GREATER THAN 72 FEET USE LS VALUES DEVELOPED BY THE DESIGN SOFTWARE.

LISTED RADIUS IS THE MINIMUM ALLOWABLE RADIUS FOR THE CORRESPONDING E, CR, AND LS VALUES.

TRANSITION CURVES - URBAN
30 MPH DESIGN SPEED