

TC-5.01

DESIGN FACTORS FOR A DESIGN SPEED OF 20 MPH (RURAL) USING E = 8% MAX.

DESIGN VELOCITY =20	DESIGN SOFTWARE EQUIVALENTS (NUMBER OF LANES AT LANE WIDTH)												INTERCHANGE RAMPS					
	WIDTH=18 FT			WIDTH=20 FT			WIDTH=22 FT			WIDTH=24 FT			WIDTH=48 FT		16 FT		18 FT	
	1 @ 9'		1 @ 10'		1 @ 11'		1 @ 12'		1 @ 12'		2 @ 12'		w		CR	LS	CR	LS
RADIUS(FT) E(%)	CR	LS	w	CR	LS	w	CR	LS	w	CR	LS	w	CR	LS	CR	LS	CR	LS
1800	NC	0	0.0	0	0	0.0	0	0	0.0	0	0	0.0	0	0	0.0	0	0	0
1213	2.0	59	2.0	28	28	0.0	30	30	0.0	33	33	0.0	49	49	0.0	39	39	41
1148	2.1	57	59	2.1	28	29	0.0	30	32	0.0	33	35	0.0	49	52	0.0	39	40
1090	2.2	54	59	2.1	28	30	0.0	30	33	0.0	33	36	0.0	49	54	0.0	39	42
1036	2.3	52	59	2.1	28	32	0.0	30	35	0.0	33	38	0.0	49	56	0.0	39	44
987	2.4	50	59	2.2	28	33	0.0	30	36	0.0	33	39	0.0	49	59	0.0	39	46
941	2.5	48	59	2.2	28	34	0.0	30	38	0.0	33	41	0.0	49	61	0.0	39	48
899	2.6	46	59	2.3	28	36	0.0	30	39	0.0	33	43	0.0	49	64	0.0	39	50
860	2.7	44	59	2.3	28	37	0.0	30	41	0.0	33	44	0.0	49	66	0.0	39	52
824	2.8	43	59	2.3	28	38	0.0	30	42	0.0	33	46	0.0	49	69	0.0	39	54
790	2.9	41	59	2.4	28	40	0.0	30	44	0.0	33	48	0.0	49	71	0.0	39	56
759	3.0	40	59	2.4	28	41	0.0	30	45	0.0	33	49	0.0	49	73	0.0	39	58
729	3.1	39	59	2.5	28	42	0.0	30	47	0.0	33	51	0.0	49	76	0.0	39	60
701	3.2	37	59	2.5	28	44	0.0	30	48	0.0	33	52	0.0	49	78	0.0	39	61
674	3.3	36	59	2.5	28	45	0.0	30	50	0.0	33	54	0.0	49	81	0.0	39	63
650	3.4	35	59	2.6	28	46	0.0	30	51	0.0	33	56	0.0	49	83	0.0	39	65
626	3.5	34	59	2.6	28	48	0.0	30	53	0.0	33	57	0.0	49	86	0.0	39	67
604	3.6	33	59	2.7	28	49	0.0	30	54	0.0	33	59	0.0	49	88	0.0	39	69
582	3.7	32	59	2.7	28	50	0.0	30	55	0.0	33	60	0.0	49	90	0.0	39	71
562	3.8	32	59	2.8	28	52	0.0	30	57	0.0	33	62	0.0	49	93	0.0	39	73
543	3.9	31	59	2.8	28	53	0.0	30	58	0.0	33	62	0.0	49	95	0.0	39	75
524	4.0	30	59	2.9	28	55	0.0	30	60	0.0	33	65	0.0	49	98	0.0	39	77
506	4.1	29	59	2.9	28	56	0.0	30	61	0.0	33	67	0.0	49	100	0.0	39	79
489	4.2	29	60	3.0	30	63	2.0	30	63	0.0	33	69	0.0	49	103	0.0	39	80
473	4.3	29	62	3.0	30	64	2.0	30	64	0.0	33	70	0.0	49	105	0.0	39	82
457	4.4	29	63	3.0	30	66	2.0	30	66	0.0	33	72	0.0	49	108	0.0	39	84
442	4.5	29	65	3.1	31	68	2.1	30	67	0.0	33	73	0.0	49	110	0.0	39	86
427	4.6	29	66	3.2	30	69	2.2	30	69	0.0	33	75	0.0	49	112	0.0	39	88
413	4.7	29	68	3.2	31	71	2.2	30	70	0.0	33	77	0.0	49	115	0.0	39	90
399	4.8	30	70	3.3	31	73	2.3	30	72	0.0	33	78	0.0	49	117	0.0	39	92
385	4.9	29	71	3.3	31	74	2.3	30	73	0.0	33	80	0.0	49	120	0.0	39	94
372	5.0	30	73	3.4	31	76	2.4	30	75	0.0	33	82	0.0	49	122	0.0	39	96
358	5.1	30	75	3.5	31	78	2.5	30	76	0.0	33	83	0.0	49	125	0.0	39	98
345	5.2	30	76	3.5	31	80	2.5	30	78	0.0	33	85	0.0	49	127	0.0	39	100
332	5.3	30	78	3.6	31	81	2.6	30	79	0.0	33	86	0.0	49	129	0.0	39	101
320	5.4	30	80	3.7	31	83	2.7	30	81	0.0	33	88	0.0	49	132	0.0	39	103
308	5.5	30	82	3.8	31	85	2.8	30	82	0.0	33	90	0.0	49	134	0.0	39	105
297	5.6	30	83	3.9	32	87	2.9	30	84	0.0	33	91	0.0	49	137	0.0	39	107
286	5.7	30	85	3.9	32	89	2.9	30	85	0.0	33	93	0.0	49	139	0.0	39	109
276	5.8	30	87	4.0	32	91	3.0	33	95	2.0	33	95	0.0	53	153	2.0	39	111
266	5.9	31	89	4.1	32	93	3.1	33	97	2.1	33	96	0.0	54	157	2.2	39	113
258	6.0	30	90	4.2	32	95	3.2	33	99	2.2	33	98	0.0	54	161	2.4	39	115
248	6.1	31	92	4.3	32	97	3.3	34	101	2.3	33	99	0.0	55	165	2.6	39	117
240	6.2	31	94	4.4	32	99	3.4	34	103	2.4	33	101	0.0	55	169	2.8	39	119
232	6.3	31	96	4.5	33	101	3.5	34	105	2.5	33	103	0.0	55	173	3.0	39	120
225	6.4	31	98	4.6	33	103	3.6	34	107	2.6	33	104	0.0	56	177	3.2	39	122
217	6.5	31	100	4.7	33	105	3.7	34	109	2.7	33	106	0.0	56	181	3.4	39	124
209	6.6	31	102	4.8	33	107	3.8	34	111	2.8	33	108	0.0	57	185	3.6	39	126
202	6.7	32	104	4.9	33	109	3.9	34	113	2.9	33	109	0.0	57	189	3.8	39	128
196	6.8	32	106	5.0	33	111	4.0	34	115	3.0	36	120	0.0	57	193	4.0	39	130
189	6.9	32	108	5.1	33	113	4.1	35	118	3.1	36	122	2.1	58	198	4.2	39	132
183	7.0	32	110	5.2	33	115	4.2	35	120	3.2	36	124	2.2	58	202	4.4	39	134
176	7.1	32	112	5.3	33	117	4.3	35	122	3.3	36	127	2.3	59	206	4.6	39	136
170	7.2	32	115	5.5	34	120	4.5	35	125	3.5	36	129	2.5	59	212	5.0	39	138
164	7.3	33	117	5.6	34	122	4.6	35	127	3.6	37	132	2.6	60	217	5.2	39	140
158	7.4	33	119	5.8	34	124	4.8	35	129	3.8	37	134	2.8	60	222	5.6	39	141
152	7.5	33	122	5.9	34	127	4.9	36	132	3.9	37	137	2.9	61	227	5.8	39	143
146	7.6	33	124	6.1	34	129	5.1	36	135	4.1	37	140	3.1	62	233	6.2	39	145
139	7.7	33	127	6.3	35	132	5.3	36	137	4.3	38	143	3.3	63	239	6.6	39	147
132	7.8	34	130	6.5	35	135	5.5	36	140	4.5	38	145	3.5	64	246	7.0	39	149
124	7.9	34	133	6.6	35	138	5.8	37	144	4.8	38	149	3.8	65	254	7.6	39	151
108	8.0	35	139	7.6	36	144	6.6	38	150	5.6	39	155	4.6	68	270	9.2	39	153

NOTE: CR, LS & w VALUES IN FEET. LISTED RADIUS IS THE MINIMUM ALLOWABLE RADIUS FOR THE CORRESPONDING E, CR, LS, AND w VALUES.

TRANSITION CURVES - RURAL  
20 MPH DESIGN SPEED

VIRGINIA DEPARTMENT OF TRANSPORTATION

REV. 3/03

802.34

SPECIFICATION  
REFERENCE