

		CORNER BRACE	LINE BRACE	LINE BRACE AT END LOCATION	FE-B
WOOD POST		<p>PAY LINES (EXCLUSIVE OF WIRE) $\frac{3}{8}$"X4" GALVANIZED STEEL DOWL (ALL ENDS) MIN. 4" BRACE 4'-6" 3'-0" 6"X6" 8'-0" 8'-0" 6"X6" 6"X6" CORNER POST #9 WIRE TWISTED</p>	<p>DIAGONAL 4" BRACE TO BE PLACED IN DIRECTION OF PULL.</p> <p>POST TO BE NOTCHED FOR DIAGONAL 4" BRACES. ALL DIAGONAL 4" BRACES TO HAVE TWO GALVANIZED 12D NAILS AT EACH END.</p> <p>6" 10" 10" 10" 16" 8'-0" PAY LINES (EXCLUSIVE OF FABRIC) GROUND LINE #9 WIRE TWISTED</p>	<p>THE BRACE WIRE TO BE PLACED AROUND POSTS WITH ONE WIRE ON EACH SIDE OF BRACE. WIRE TO BE DRAWN TAUT BY TWISTING BETWEEN BRACE AND EACH POST. THIS APPLIES TO ALL BRACE WIRES.</p> <p>$\frac{3}{8}$"X4" GALVANIZED STEEL DOWELS 4" 6" 6" 4'-6" 4 POINT BARBED WIRE GROUND LINE 12'-0" (TYP. SPACING BETWEEN ALL LINE POSTS) 8'-0" BRACE POST PAY LINES (EXCLUSIVE OF FABRIC)</p>	
		<p>IF NOT OTHERWISE NOTED DIMENSIONS AND DESCRIPTIONS SHOWN ON ONE DRAWING APPLY TO OTHER DETAILS WITH THE SAME POST TYPE.</p>			
METAL POST		<p>* L2$\frac{1}{2}$X2$\frac{1}{2}$X$\frac{1}{4}$ POST WITH L2X2X$\frac{3}{16}$X7'-0" BRACES OR 2$\frac{1}{2}$" O.D. POST @ 3.65+5% LBS./FT. WITH 1$\frac{5}{8}$" O.D. BRACES @ 2.27 ± 5% LBS./FT.</p> <p>4'-6" 2'-6" 12'-0" 6'-0" 6'-0" 12'-0" 3'-0" CORNER POST CONCRETE FOOTING</p>	<p>1'-6" 4 POINT BARBED WIRE 10" 10" 10" 16" 6'-0" 6'-0" STRETCHER POST 12" 12"X12"X12" CONCRETE BLOCK</p>	<p>* 4'-6" 2'-6" 12'-0" (TYPICAL SPACING BETWEEN ALL LINE POSTS) 4'-6" 3'-0" 12"X12"X12" CONC. BLOCK 12'-0" LINE POST (SEE DETAIL BELOW) PAY LINES (EXCLUSIVE OF FABRIC)</p>	
		<p>FLANGED "U" TYPE "T" TYPE</p> <p>LINE POSTS ARE TO BE OF THE TYPES SHOWN OR EQUIVALENT MEETING THE APPROVAL OF THE ENGINEER.</p> <p>ALL POSTS ARE TO HAVE A MINIMUM WEIGHT OF 1.25 LBS./FT.</p> <p>A MINIMUM OF FIVE CLAMPS FOR ATTACHING FABRIC TO POST ARE TO BE INCLUDED IN COST OF EACH LINE POST.</p> <p>NOTES: SEE GENERAL NOTES FENCING FOR ADDITIONAL DETAILS AND INSTRUCTIONS.</p> <p>METAL LINE POST</p>	<p>L2X2X$\frac{3}{16}$ TO BE CUT TO FIT AROUND L2$\frac{1}{2}$X2$\frac{1}{2}$X$\frac{1}{4}$ STRETCHER POST. L2$\frac{1}{2}$X2$\frac{1}{2}$X$\frac{1}{4}$, 2" LONG BRACKET BOLTED TO STRETCHER POST</p> <p>ALTERNATE</p> <p>METHOD OF ATTACHING ANGLE BRACES TO STRETCHER POSTS</p>	<p>FOR USE IN LIEU OF SETTING POSTS IN CONCRETE. DEVICES SHOWN ARE REPRESENTATIONAL ONLY. SEE GENERAL NOTES.</p> <p>ALTERNATE ANCHOR DEVICES</p>	
SPECIFICATION REFERENCE	<h2>STANDARD FENCE</h2> <h3>BARBED WIRE</h3> <p>VIRGINIA DEPARTMENT OF TRANSPORTATION</p>			<p>ROAD AND BRIDGE STANDARDS</p>	
242 507 236				REVISION DATE	SHEET 1 OF 1 503.03