## ACCESSIBLE PARKING AND PASSENGER LOADING ZONES\* 4 **ACCESSIBLE ROUTE** HARED ACCESS AISLE 21'MIN. MINIMUM DIMENSIONS FOR ACCESSIBLE PARKING ## Universal Parking Spaces 20' MIN. 11' wide may be used. See instructions for "Parking Spaces" to determine number **ACCESS AISLE** of accessible spaces required. #8' min. adjacent to spaces for vane designed for handicapped persons.

## ACCESS AISLE FOR ACCESSIBLE LOADING ZONES

Source: The most recent Americans with Disabilities Act Accessibility Guidelines (ADAAG). **NOTES:** 

**LOCATION:** Parking spaces for persons with mobility impairments and accessible passenger loading zones that serve a particular building shall be located on the shortest possible accessible circulation route to an accessible entrance of the building. In separate parking structures or lots that do not serve a particular building, accessible parking spaces shall be located on the shortest possible circulation route to an accessible pedestrian entrance of the parking facility.

**PASSENGER LOADING ZONES:** If there are curbs between the access aisle and the vehicle pull-up space, then a Standard CG-12 Curb Ramp shall be provided.

## FIGURE C-1-10.1 DESIGNS FOR ACCESSIBLE PARKING SPACES

<sup>\*</sup> Rev. 1/08