

## SURVEY BASELINE

All survey baselines are to be shown in accordance with CADD Standards. Circles are to be shown at each intersection point of two or more survey lines, having these points as the center. **Station marks** are to be shown at 100 feet (20 meter)-Rural, and 50 foot (10 meter)-Urban intervals, perpendicular to the survey baseline and extending approximately  $\frac{1}{10}$  inch (3 mm) left and right. The **500 feet (100 meter) station marks** are to be labeled with the station number equal distances to the left and at a distance adequate to clear anticipated proposed right of way.

## MATCH LINES

Match lines are to be shown perpendicular to the construction baseline at even construction stations. Stations and adjacent sheet number are to be shown at the beginning and end of each applicable plan sheet and at necessary points on connection and traverse baselines.

## BEARINGS

**Bearings** are to be shown on each tangent or sub tangent segment on each plan sheet. If a tangent line extends for over half the length of the plan sheet, the bearing should be shown twice at equal intervals. Bearings should be shown so as not to conflict with station marks.

## CURVE DATA

T.S.'s, S.C.'s C.S.'s, and S.T.'s on curves with spirals and P.C.'s and P.T.'s on curves without spirals are to be **labeled along lines** projecting from these points toward the center of the curve at a distance from the baseline adequate to clear anticipated proposed items and topography. P.R.C. lines may be projected toward either curve center point. Labeling is to be at an adequate distance from the baseline to clear anticipated proposed items and topography. **Remaining curve data** (degree; tangent; length; radius; curve stations superelevation rate (E) and superelevation runoff ( $L_r$ )\* ) are to be shown on the inside of the curve, centered longitudinally and lettered along imaginary lines parallel to a line that would be tangent to the mid point of the curve. **Superelevation runoff ( $L_r$ ) information is to be placed manually in the curve data.** **Curve data** is to be shown as closely to the baseline as practicable, but beyond anticipated proposed items and topography. **Complete curve data** is to be shown on each sheet on which any portion of the curve appears. Curve data, including stations may, if necessary due to congestion, be located in other appropriate areas of the plan sheet. In these cases, the curve itself and the data are to be identified with **a number** ("1", "2", "3", etc.) inside a  $\frac{1}{4}$  inch (6 mm) circle for existing and  $\frac{5}{16}$  inch (8 mm) circle for proposed curve data.

---

\* Rev. 1/11