

SECTION C-3 RIGHT OF WAY

POLICY*

The type of Right of Way Monuments to be used will be determined at the Field Inspection.

The District Engineer's Field Inspection Report will indicate whether concrete Right of Way Monuments, Std. RM-1, or steel pin Right of Way Monuments, St'd. RM-2, are to be used.

When both types are recommended, the location of each type will be specified.

ST'D RM-1

The St'd. Right of Way Monument, St'd. RM-1, is concrete and will be used at locations as recommended by the District Administrator at the Field Inspection.

St'd RM-1 monuments shall be set by the contractor.

ST'D RM-2

The St'd. Right of Way Monument, St'd. RM-2 uses a steel pin with cap and locator post.

The St'd. RM-2 monument is not a replacement for the concrete monument (St'd. RM-1), but will be used at locations as recommended by the District Administrator at the Field Inspection.

St'd. RM-2 monuments will be set by the Contractor when Construction Surveying is to be performed by contract.

St'd. RM-2 monuments will be set by the State Survey Party only after approval by the State Location and Design Engineer, in accordance with IIM-LD-152.

GENERAL NOTES

General Notes are to be shown in accordance with IIM-LD-110.

PLANS

Projects containing both types of monuments should have each type clearly noted.

* Added 7/08