

Average Motor Vehicle Operating Speed	Average Annual Daily Traffic (AADT) Volume											
	less than 2,000				2,000-10,000				over 10,000			
	Adequate Sight Distance		Inadequate Sight Distance		Adequate Sight Distance		Inadequate Sight Distance		Adequate Sight Distance		Inadequate Sight Distance	
less than 30 mph	Truck, Bus, Rv				Truck, Bus, Rv				Truck, Bus, Rv			
		wc	wc	wc	wc	wc	wc	wc	wc	bl	bl	bl
	14	14	14	14	14	14	14	14	5	5	5	5
30-40 mph	bl	bl	bl	bl	bl	bl	bl	bl	bl	bl	bl	bl
	5	5	5	5	5	6	6	5	6	6	6	6
41-50 mph	bl	bl	bl	bl	bl	bl	bl	bl	bl	bl	bl	bl
	6	6	6	6	6	6	6	6	6	6	6	6
over 50 mph	na	na	na	na	na	na	na	na	na	na	na	na

TABLE A-5-5

GROUP B/C BICYCLISTS, URBAN SECTION, WITH PARKING

(widths are in feet)

For Table A-5-5: wc and sl widths represent “usable widths” of outer lanes, measured from the left edge of the parking space (8 to 10 ft. minimum from the curb face) to the left stripe of the travel lane.

Key: wc = wide curb lane; sh = shoulder; sl = shared lane; bl = bike lane; na = not applicable; truck, buses. And/or recreation vehicles (approximately 30 per hour or more).