

FE-W1,W2	CORNER BRACE	LINE BRACE	LINE BRACE AT END LOCATION
WOOD POST			<p>THE BRACE WIRE TO BE PLACED AROUND POSTS WITH ONE WIRE ON EACH SIDE OF BRACE. WIRE TO BE DRAWN TAUT BY TWISTING BETWEEN BRACE AND EACH POST. THIS APPLIES TO ALL BRACE WIRES.</p> <p>DIAGONAL 4" BRACES TO BE PLACED IN DIRECTION OF PULL. POST TO BE NOTCHED FOR DIAGONAL 4" BRACES. ALL 4" DIAGONAL BRACES TO HAVE TWO GALVANIZED 12D NAILS AT EACH END.</p>
METAL POST	<p>* L2/2x2/2x1/4 POST WITH 2X2x3/16x7'-0" BRACES OR 2 1/2" O.D. POST @ 3.65 ± 5% LBS./FT WITH 1 1/8" O.D. BRACES @ 2.27 ± 5% LBS./FT</p>	<p>IF NOT OTHERWISE NOTED DIMENSIONS AND DESCRIPTIONS SHOWN ON ONE DRAWING APPLY TO OTHER DETAILS WITH THE SAME POST TYPE.</p>	
<p><b>NOTES:</b></p> <p>SEE GENERAL NOTES-FENCING FOR ADDITIONAL DETAILS AND INSTRUCTIONS.</p>	<p>LINE POSTS ARE TO BE OF THE TYPES SHOWN OR EQUIVALENT MEETING THE APPROVAL OF THE ENGINEER.</p> <p>ALL POSTS ARE TO HAVE A MINIMUM WEIGHT OF 1.25 LBS./FT.</p> <p>A MINIMUM OF FIVE CLAMPS FOR ATTACHING FABRIC TO POST ARE TO BE INCLUDED IN COST OF EACH LINE POST.</p> <p>FLANGED "U" TYPE "T" TYPE</p> <p>METAL LINE POST</p>	<p>FOR USE IN LIEU OF SETTING POSTS IN CONCRETE. DEVICES SHOWN ARE REPRESENTATIONAL ONLY, SEE GENERAL NOTES.</p> <p>ALTERNATE ANCHOR DEVICES</p>	<p>L2X2X3/16 TO BE CUT TO FIT AROUND L2/2X2/2X1/4 STRETCHER POST.</p> <p>L2/2X2/2X1/4, 2" LONG BRACKET BOLTED TO STRETCHER POST.</p> <p>METHOD OF ATTACHING ANGLE BRACES TO STRETCHER POSTS</p>
<p><b>STANDARD FENCE WOVEN WIRE FABRIC</b></p> <p>VIRGINIA DEPARTMENT OF TRANSPORTATION</p>			<p>SPECIFICATION REFERENCE</p> <p>242 507 236</p>