

DIMENSIONS					REINFORCING STEEL																						
SPAN	HGHT	T1	T2	T3	BH1						BH2			BH3			BV1			NO. BL1 BARS	NO. BL2 BARS						
(FT.)	(FT.)	TOP SLAB (IN.)	BOTTOM SLAB (IN.)	WALL (IN.)	A	B	C	D	E	F	SIZE	SPACING C-C	a	b	LENGTH	SIZE	SPACING C-C	LENGTH	SIZE			SPACING C-C	a	LENGTH	SIZE	SPACING C-C	LENGTH
12	14	25/4"	25/4"	12"	11	11'- 0"	11	11'- 0"	12	12'- 0"	5	5"	13'- 8"	9'- 7/4"	32'- 3"	8	5"	13'- 8"	4	5"	4'- 2 3/4"	8'- 2"	5	5"	17'- 11"	52	52
12	16	25/4"	25/4"	13 3/4"	11	11'- 0"	11	11'- 0"	14	14'- 0"	6	4 1/2"	13'- 11 1/2"	10'- 7 1/4"	34'- 4"	9	4 1/2"	14'- 0"	3	4 1/2"	4'- 4 1/2"	8'- 7"	7	8 1/2"	19'- 11"	52	60
14	8	28 3/4"	28 3/4"	10 1/2"	13	13'- 0"	13	13'- 0"	6	6'- 0"	4	4 1/2"	15'- 5"	6'- 10 3/4"	28'- 8"	8	4 1/2"	15'- 5"	--	---	-----	-----	4	12"	12'- 5"	60	28
14	10	28 1/2"	28 1/2"	9 3/4"	13	13'- 0"	13	13'- 0"	8	8'- 0"	4	4 1/2"	15'- 3 1/2"	7'- 10 1/2"	30'- 6"	8	4 1/2"	15'- 3"	3	4 1/2"	4'- 5 3/8"	8'- 8"	6	11 1/2"	14'- 5"	60	36
14	12	28 1/2"	28 1/2"	10 1/2"	13	13'- 0"	13	13'- 0"	10	10'- 0"	4	4 1/2"	15'- 5"	8'- 10 1/2"	32'- 8"	8	4 1/2"	15'- 5"	4	4 1/2"	4'- 6 1/8"	8'- 9"	5	6"	16'- 5"	60	44
14	14	28 1/2"	28 1/2"	12 1/4"	13	13'- 0"	13	13'- 0"	12	12'- 0"	5	4 1/2"	15'- 8 1/2"	9'- 10 1/2"	34'- 10"	9	4 1/2"	15'- 8"	3	4 1/2"	4'- 7 7/8"	9'- 1"	7	10 1/2"	18'- 5"	60	52
14	16	28 1/2"	28 1/2"	13 3/4"	13	13'- 0"	13	13'- 0"	14	14'- 0"	6	4 1/2"	15'- 11 1/2"	10'- 10 1/2"	36'- 11"	9	4 1/2"	15'- 11"	3	4 1/2"	4'- 9 3/8"	9'- 4"	6	6 1/2"	20'- 5"	60	60

SPAN	HGHT	REINFORCING STEEL (LBS/LONG. JT)	QUAN./LF		HEADWALLS											
			CONCRETE CLASS A4 (CY/LF)	REINFORCING STEEL (LBS/LF)	G		HW 1		INLET CONCRETE CL. A4 (CY)	INLET REINFORCING STEEL (LBS)	OUTLET CONCRETE CL. A4 (CY)	OUTLET REINFORCING STEEL (LBS)	WINGWALL			
(FT.)	(FT.)				HEADWALL LENGTH	SIZE	LENGTH									
12	14	61.776	3.221	532.966	14'-10"	6	14'- 6"	2.205	87.116	2.236	87.116	Z				
12	16	64.600	3.572	735.565	14'-10"	6	14'- 6"	2.124	87.116	2.153	87.116	DD				
14	8	59.984	3.326	388.860	16'-10"	6	16'- 6"	1.917	99.132	1.955	99.132	O				
14	10	62.808	3.358	459.387	16'-10"	6	16'- 6"	2.147	99.132	2.186	99.132	S				
14	12	65.632	3.551	523.375	16'-10"	6	16'- 6"	2.234	99.132	2.272	99.132	W				
14	14	68.456	3.873	659.960	16'-10"	6	16'- 6"	2.187	99.132	2.224	99.132	AA				
14	16	71.280	4.206	797.650	16'-10"	6	16'- 6"	2.129	99.132	2.165	99.132	EE				

For Typical Section, notes and other details, refer to Standard BCB-DT.