

SECTION
800

TRANSITION
CURVES

Tables of Contents
Road and Bridge Standards - Section 800: Transition Curves

| Standard | Page | Title | Current Revision | Previous Revisions | | | | | Original Standard | Insertable Sheet |
|----------|--------|---|----------------------|----------------------|--|--|--|--|----------------------|------------------|
| TC-5 | 801.01 | Transition Curves for Rural and Urban Highways and Street Conditions | 1/07 | | | | | | 2/01 | |
| | 801.02 | Explanation of Tables and Instructions for use - Urban Condition | 1/07 | | | | | | 2/01 | |
| | 801.03 | Explanation of Tables and Instructions for use - Rural Condition | 1/07 | | | | | | 2/01 | |
| | 801.04 | Explanation of Tables and Instructions for use - General Condition | 1/07 | | | | | | 2/01 | |
| | 801.05 | Details for Transitioned Baseline Rural Condition with Pavement Widening | 1/07 | | | | | | 2/01 | |
| | 801.06 | Details for Non-Transitioned Baseline Urban Condition and Rural Condition Without Pavement Widening | 1/07 | | | | | | 2/01 | |
| | 801.07 | Details of Superelevation About Baseline | 1/07 | | | | | | 2/01 | |
| | 801.08 | Details of Superelevation About Baseline | | | | | | | 2/01 | |
| | 801.09 | Example for Four Lane Roadways | 1/07 | | | | | | 2/01 | |
| | 801.10 | Cross Section - Four Lane Roadways | | | | | | | 2/01 | |
| | 801.11 | Method of Applying TC-5 on Compound and Reverse Curves Rural Condition Only With Pavement Widening | 1/07 | | | | | | 2/01 | |
| | 801.12 | Crown Transition / Crown Runoff (CR) Table | 1/07 | 7/01 | | | | | 2/01 | |
| | 801.13 | Table 1 | 1/07 | | | | | | 2/01 | |
| | 801.14 | Table 2 | 1/07 | | | | | | 2/01 | |
| | 801.15 | Design Superelevation Rates Urban Conditions | | | | | | | 2/01 | |
| | 801.16 | Design Superelevation Rates Rural Conditions | | | | | | | 2/01 | |
| | 801.17 | Methodologies for Calculating TC-5 Values for Urban Low-Speed Streets | 1/07 | | | | | | 2/01 | |
| | 801.18 | Methodologies for Calculating TC-5 Values | 1/07 | | | | | | 2/01 | |

Tables of Contents
Road and Bridge Standards - Section 800: Transition Curves

| Standard | Page | Title | Current Revision | Previous Revisions | | | | | | Original Standard | Insertable Sheet |
|----------|---|--|----------------------|--------------------|--|--|--|--|----------------------|----------------------|------------------|
| TC-5 | 801.19 | Calculated TC-5 Examples | 1/07 | | | | | | | 2/01 | |
| | 801.20 | Summary of Standard TC-5ULS (Urban Low Speed) Design Factors | 1/07 | | | | | | | 2/01 | |
| | 801.21 | Design Factors for a Design Speed of 20 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.22 | Design Factors for a Design Speed of 25 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.23 | Design Factors for a Design Speed of 30 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.24 | Design Factors for a Design Speed of 35 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.25 | Design Factors for a Design Speed of 40 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.26 | Design Factors for a Design Speed of 45 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.27 | Design Factors for a Design Speed of 50 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.28 | Design Factors for a Design Speed of 55 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.29 | Design Factors for a Design Speed of 60 mph (Urban) | 1/07 | | | | | | | 2/01 | |
| | 801.30 | Design Factors for a Design Speed of 20 mph (Rural) | 1/07 | | | | | | | 2/01 | |
| | 801.31 | Design Factors for a Design Speed of 25 mph (Rural) | 1/07 | | | | | | | 2/01 | |
| | 801.32 | Design Factors for a Design Speed of 30 mph (Rural) | 1/07 | | | | | | | 2/01 | |
| | 801.33 | Design Factors for a Design Speed of 35 mph (Rural) | 1/07 | | | | | | | 2/01 | |
| | 801.34 | Design Factors for a Design Speed of 40 mph (Rural) | 1/07 | | | | | | | 2/01 | |
| | 801.35 | Design Factors for a Design Speed of 45 mph (Rural) | 1/07 | | | | | | | 2/01 | |
| 801.36 | Design Factors for a Design Speed of 50 mph (Rural) | 1/07 | | | | | | | 2/01 | | |
| 801.37 | Design Factors for a Design Speed of 55 mph (Rural) | 1/07 | | | | | | | 2/01 | | |

Tables of Contents
Road and Bridge Standards - Section 800: Transition Curves

| Standard | Page | Title | Current Revision | Previous Revisions | | | | | Original Standard | Insertable Sheet |
|----------|---|---|----------------------|--------------------|--|--|--|-----------------------|-----------------------|------------------|
| TC-5 | 801.38 | Design Factors for a Design Speed of 60 mph (Rural) | 1/07 | | | | | | 2/01 | |
| | 801.39 | Design Factors for a Design Speed of 65 mph (Rural) | 1/07 | | | | | | 2/01 | |
| | 801.40 | Design Factors for a Design Speed of 70 mph (Rural) | 1/07 | | | | | | 2/01 | |
| TC-5.01 | 802.01 | Transition Curves for Rural and Urban Highways and Street Conditions | 1/07 | | | | | | 10/02 | |
| | 802.02 | Explanation of Tables and Instructions for use - Urban Condition | 1/07 | | | | | | 10/02 | |
| | 802.03 | Explanation of Tables and Instructions for use - Rural Condition | 1/07 | | | | | | 10/02 | |
| | 802.04 | Explanation of Tables and Instruction for use - General Condition | 1/07 | | | | | | 10/02 | |
| | 802.05 | Details for Transitioned Baseline Rural Condition with Pavement Widening | 1/07 | | | | | | 10/02 | |
| | 802.06 | Details for Non-Transitioned Baseline Urban Condition and Rural Condition Without Pavement Widening | 1/07 | | | | | | 10/02 | |
| | 802.07 | Details of Superelevation About Baseline | 1/07 | | | | | | 10/02 | |
| | 802.08 | Details of Superelevation About Baseline | | | | | | | 10/02 | |
| | 802.09 | Example for Four Lane Roadways | 1/07 | | | | | | 10/02 | |
| | 802.10 | Cross Section - Four Lane Roadways | | | | | | | 10/02 | |
| | 802.11 | Method of Applying TC-5.01 on Compound Curves Rural Condition With Pavement Widening | | | | | | | 10/02 | |
| 802.12 | Method of Applying TC-5.01 on Reverse Curves Rural Condition With Pavement Widening | 1/07 | | | | | | 10/02 | | |
| 802.13 | Method of Applying TC-5.01 on Compound Curves Urban & Rural Condition Without Pavement Widening | 1/07 | 3/03 | | | | | 10/02 | | |

Tables of Contents
Road and Bridge Standards - Section 800: Transition Curves

| Standard | Page | Title | Current Revision | Previous Revisions | | | | | | Original Standard | Insertable Sheet |
|----------|---|--|----------------------|----------------------|----------------------|--|--|--|-----------------------|-----------------------|------------------|
| TC-5.01 | 802.14 | Method of Applying TC-5.01 on Reverse Curves Urban & Rural Condition Without Pavement Widening | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.15 | Blank Sheet | | | | | | | | 10/02 | |
| | 802.16 | Crown Transition / Crown Runoff (CR) Table | 1/07 | | | | | | | 10/02 | |
| | 802.17 | Table 1 | 1/07 | | | | | | | 10/02 | |
| | 802.18 | Table 2 | 1/07 | | | | | | | 10/02 | |
| | 802.19 | Design Superelevation Rates Urban Conditions | | | | | | | | 10/02 | |
| | 802.20 | Design Superelevation Rates Rural Conditions | | | | | | | | 10/02 | |
| | 802.21 | Methodologies for Calculating TC-5.01 Values for Urban Low-Speed Streets | 1/07 | 7/05 | 7/03 | | | | | 10/02 | |
| | 802.21A | Methodologies for Calculating TC-5.04 Values for Urban Low-Speed Streets | 1/07 | | | | | | | 2/06 | |
| | 802.22 | Methodologies for Calculating TC-5.01 Values | 1/07 | 7/03 | 3/03 | | | | | 10/02 | |
| | 802.23 | Calculated TC-5.01 Examples | 1/07 | | | | | | | 10/02 | |
| | 802.24 | Summary of Standard TC-5.01 ULS (Urban Low Speed) Design Factors | 1/07 | 7/05 | | | | | | 10/02 | |
| | 802.24A | Summary of Standard TC-5.04 ULS (Urban Low Speed) Design Factors | 1/07 | | | | | | | 2/06 | |
| | 802.25 | Design Factors for a Design Speed of 20 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| | 802.26 | Design Factors for a Design Speed of 25 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| | 802.27 | Design Factors for a Design Speed of 30 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| 802.28 | Design Factors for a Design Speed of 35 mph (Urban) | 1/07 | | | | | | | 10/02 | | |
| 802.29 | Design Factors for a Design Speed of 40 mph (Urban) | 1/07 | | | | | | | 10/02 | | |

Tables of Contents
Road and Bridge Standards - Section 800: Transition Curves

| Standard | Page | Title | Current Revision | Previous Revisions | | | | | | Original Standard | Insertable Sheet |
|----------|--------|---|----------------------|----------------------|----------------------|--|--|--|--|-----------------------|------------------|
| TC-5.01 | 802.30 | Design Factors for a Design Speed of 45 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| | 802.31 | Design Factors for a Design Speed of 50 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| | 802.32 | Design Factors for a Design Speed of 55 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| | 802.33 | Design Factors for a Design Speed of 60 mph (Urban) | 1/07 | | | | | | | 10/02 | |
| | 802.34 | Design Factors for a Design Speed of 20 mph (Rural) | 1/07 | 1/04 | 3/03 | | | | | 10/02 | |
| | 802.35 | Design Factors for a Design Speed of 25 mph (Rural) | 1/07 | 1/04 | 3/03 | | | | | 10/02 | |
| | 802.36 | Design Factors for a Design Speed of 30 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.37 | Design Factors for a Design Speed of 35 mph (Rural) | 1/07 | 1/04 | 3/03 | | | | | 10/02 | |
| | 802.38 | Design Factors for a Design Speed of 40 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.39 | Design Factors for a Design Speed of 45 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.40 | Design Factors for a Design Speed of 50 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.41 | Design Factors for a Design Speed of 55 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.42 | Design Factors for a Design Speed of 60 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.43 | Design Factors for a Design Speed of 65 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |
| | 802.44 | Design Factors for a Design Speed of 70 mph (Rural) | 1/07 | 3/03 | | | | | | 10/02 | |