

CULVERT SIZE DIAMETER (in.)	1 ½ : 1 Slope				2 : 1 Slope			
	EC-3 Type B	Depth (T) (18") Class A1	Depth (T) (24") Class I	Depth (T) (36") Class II	EC-3 Type B	Depth (T) (18") Class A1	Depth (T) (24") Class I	Depth (T) (36") Class II
	Sq. Yds.	Cu. Yds.	Cu. Yds.	Cu. Yds.	Sq. Yds.	Cu. Yds.	Cu. Yds.	Cu. Yds.
42	26.09	13.04	17.39	26.09	24.54	12.27	16.36	24.54
48	34.11	17.06	22.74	34.11	32.07	16.04	21.38	32.07
54	43.20	21.60	28.80	43.20	40.61	20.30	27.07	40.61
60	53.34	26.67	35.56	53.34	49.50	24.75	33.00	49.50
66	64.85	32.42	43.23	64.85	60.71	30.35	40.47	60.71
72	76.89	38.45	51.26	76.89	72.27	36.14	48.18	72.27
78	90.27	45.14	60.18	90.27	70.83	35.42	47.22	70.83
84	104.70	52.35	69.80	104.70	98.42	49.21	65.61	98.42

TABLE D-9 CULVERT OUTLET PROTECTION WITH ST'D. EW-2S ENDWALLS (30° SKEW)

CULVERT SIZE DIAMETER (in.)	Increments For Each Additional Pipe			
	EC-3 Type B	Depth (T) (18") Class A1	Depth (T) (24") Class I	Depth (T) (36") Class II
	Conc.	Conc.	Conc.	Conc.
	Sq. Yds.	Cu. Yds.	Cu. Yds.	Cu. Yds.
42	13.46	6.73	8.98	13.46
48	17.50	8.75	11.66	17.50
54	22.15	11.06	14.76	22.15
60	27.25	13.61	18.17	27.25
66	32.95	16.46	21.96	32.95
72	39.15	19.56	26.10	39.15
78	45.85	22.91	30.57	45.85
84	53.15	26.56	35.43	53.15

TABLE D-10 CULVERT OUTLET PROTECTION WITH ST'D. EW-7S ENDWALLS (30° SKEW)

Quantities To Be Used Only For Computations of Dry Rip Rap For Outlet Protection.*

* Rev. 7/10