

STORM SEWER SYSTEM - Drainage system installed to carry storm water runoff, consisting of two or more pipes in a series connected by one or more drop inlets.

SUBSTRUCTURE - That part of a bridge structure below the bearings of simple and continuous spans, skewbacks of arches and top of footings of rigid frames; including backwalls, wingwalls and wing protection railings.

SUPERSTRUCTURE - That part of a bridge structure above the bearings of simple and continuous spans, skewbacks of arches and top of footings of rigid frames; excluding backwalls, wingwalls and wing protection railings.

U

UNSUITABLE MATERIAL - Material that is not adequate for use in the normal roadway prism, but may be used in other areas on the project.

V

VEHICLE -

Bus - A motor vehicle designed for the transportation of more than 10 persons.

Design vehicle - A selected motor vehicle, the weight, dimensions and operating characteristics of which are used in highway design.

House trailer - A trailer or semitrailer which is designed, constructed and equipped as a dwelling place, living abode or sleeping place either permanently or temporarily and is equipped for use as a conveyance on streets and highways.

Light delivery truck - A single unit truck, such as a panel or pick-up truck, with size and operating characteristics similar to those of a passenger car and commonly used for short-haul light delivery service. For capacity analysis purposes it is considered to be a passenger car.

Parked vehicle - A vehicle stopped for temporary storage.

Passenger Car - A motor vehicle, except motorcycles, designed for carrying 10 passengers or less and used for the transportation of persons.

Semitrailer - A vehicle designed for carrying persons or property and for being drawn by a motor vehicle and so constructed that some part of its weight and that of its load rests upon or is carried by another vehicle.