

EXCEPTION: Parking spaces used exclusively for buses, trucks, other delivery vehicles, law enforcement vehicles, or vehicular impound shall not be required to comply with **208** provided that lots accessed by the public are provided with a passenger loading zone complying with **503**.\*

### Minimum Number (R208.2)

Parking spaces complying with **502** shall be provided in accordance with Table C-1-2 except as required by **208.2.1**, **208.2.2**, and **208.2.3**. Where more than one parking facility is provided on a site, the number of accessible spaces provided on the site shall be calculated according to the number of spaces required for each parking facility.

### Van Parking Spaces (R208.2.4)

For every six or fraction of six accessible parking spaces required by **208.2** to comply with **502**, at least one shall be a “van” parking space complying with **502**.

Total Number of Parking Spaces Provided in Parking Facility	Minimum Number of Required Accessible Parking Spaces	
	Accessible Parking Spaces	Van-Accessible Parking Spaces
1 to 25	1	1
26 to 50	2	1
51 to 75	3	1
76 to 100	4	1
101 to 150	5	1
151 to 200	6	1
201 to 300	7	2
301 to 400	8	2
401 to 500	9	2
501 to 1000	2 percent of total	1 for each 6 Accessible Spaces, or fraction thereof
1001 and over	20, plus 1 for each 100, or fraction thereof, over 1000	

**TABLE C-1-2 PARKING SPACES**

Sources: 2010 ADA Standards for Accessible Design dated September 15, 2010

\* Rev. 1/15